



TECHNICAL DATA

BEY123-06

ZINSSER® BULLS EYE 1-2-3® AEROSOL PRIMER

DESCRIPTION AND USES

Zinsser® Bulls Eye 1-2-3® Aerosol Primer is a high-hiding, all purpose, primer-sealer, and stain blocker that provides up to 20% more coverage than competitive products. It blocks and seals stains caused by water, nicotine, smoke, tannin, pencil, ink, grease and felt marker, and seals smoke and pet odors. It is suitable for use on any interior or exterior wood, concrete, drywall, or non-galvanized metal, including hard-to-paint surfaces such as railings, shutters, and outdoor furniture. It is ideal for sealing spackle, drywall repairs, and hiding dark colors. It has excellent adhesion to glossy paint, glass, and ceramic tile.

PERFORMANCE CHARACTERISTICS

- Blocks tough stains
- Smooth finish
- Seals odors
- Sticks to all surfaces
- Drives in minutes, can be recoated in 1 hour

PRODUCT

SKU	DESCRIPTION
2008	Bright White 13 oz. Aerosol
290971	Gray 13 oz. Aerosol

PRODUCT APPLICATION

SURFACE PREPARATION

Surfaces should be clean, dry, sound, and free of dirt, grime, grease, oil, wax, mildew, wallpaper adhesive or any contamination that may interfere with adhesion. Remove loose paint and rust with a wire brush or sandpaper.

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

Do not spray indoors. Use at room temperature (70°F) in a well-ventilated area. Avoid high humidity. Shake can vigorously for one minute after the mixing ball begins to rattle. Turn can upside down and continue shaking for one minute. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 10-12" from surface and spray with short 'dusting' strokes. Keep the can the same distance from the surface. Keep the can in motion while spraying. To permanently block heavy odors, use Zinsser BIN® Ultimate Stain Blocker. **Do not use near open flame.**

DRY TIME & RECOAT

Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 5 minutes and can be topcoated in 30 minutes with latex or oil-based paints. For best results, allow primer to cure overnight before applying strong solvent-based topcoats.

CLEAN-UP

Wipe off tip before storing. Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

TECHNICAL DATA

BEY123-06



ZINSSER® BULLS EYE 1-2-3®

AEROSOL PRIMER

PHYSICAL PROPERTIES

	BULLS EYE 1-2-3 PRIMER WHITE	BULLS EYE 1-2-3 PRIMER GRAY
Resin Type	Modified alkyd	
Pigment Type	Titanium Dioxide	Titanium Dioxide, Calcium Carbonate, Talc
Solvents	Acetone, Aliphatic Hydrocarbons	
MIR	0.70 Max	
Fill Weight	13 ounces	
Wet Film to Achieve DFT	2 wet coats	
Practical Coverage at Recommended DFT (assume 15% material loss)	8-10 sq. ft./can (0.7-0.9 m ² /can)	
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	5 minutes
	Topcoat	30 minutes
Flash Point	-156°F (-104°C)	
Safety Information	For additional information, see SDS	

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061

Phone: 888-855-1774
www.rustoleum.com/zinsser

Form: GDH-451
Rev.: 020725