

BT 100



NON-ADHESIVE BARRICADE TAPE



TYPICAL APPLICATIONS

- For marking restricted areas and managing access to work sites by professionals in the safety, construction, utilities, hardware and other industries

PRODUCT FEATURES

- 2-inch letters are easy to read
- Resists sagging, even when stretched over long distances
- Resistant to moisture and humidity
- Stays pliant in cold temperatures
- Reusable
- Available in a variety of warning messages including: Danger, Wet Paint, Lead Hazard, and Caution

CONSTRUCTION

Overall Grade/Function: General Purpose
Backing: Polyethylene plastic
Adhesive: None

STANDARD WIDTH(S)

3 in

STANDARD LENGTH(S)

300 ft 1000 ft

Contact your Shurtape sales representative for other available sizes

STANDARD CORE SIZE

3 in

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



DANGER
(RED)



WET PAINT
(YEL)



LEAD HAZARD
(WHI)



CAUTION
(YEL)

PHYSICAL PROPERTIES STANDARD METRIC

Thickness	2-3 mils	0.05-0.08 mm
-----------	----------	--------------

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

