



PORTABLE FIRE EXTINGUISHERS

20 LB. Standard Stored Pressure Fire Extinguisher

DESCRIPTION

Buckeye's 20 lb. Standard (STD) Fire Extinguisher is a high-performance fire extinguisher utilizing a sodium bicarbonate-based extinguishing agent, one of the most effective agents for Class B and Class C fires.

Typical uses: For flammable liquid hazards in public areas such as offices, classrooms, multi-family residences, and parking garages. For flammable liquid fires in commercial operations such as industrial facilities, sanitation facilities, vehicle service centers, and healthcare facilities.

FEATURES

- Manufactured in accordance with ANSI/UL 299 and ANSI/UL 711 Standards. UL and ULC Listed.
- DOT and TC Compliant. US Coast Guard Approved with Vehicle Bracket Model 811.
- Polyester epoxy powder coated steel cylinder with all-metal valve assembly, operating lever, and handle.
- Color coded pressure gauge for easy verification of pressure status.
- Rechargeable for repeated usage.
- Trilingual labels; English, Spanish, and French
- Standard dry chemical is available in 50 lb. Pails for recharging Buckeye extinguishers.

SPECIFICATIONS

Agent Capacity: 20 lbs. / 9.07 kg

UL/ULC Rating: 120B:C

Shipping Weight: 33.5 lbs. / 15.2 kg

Height: 21.25 in / 53.8 cm

Width: 8.75 in / 22.2 cm

Cylinder Diameter: 7.5 in / 19.1 cm

Discharge Time: 28 seconds

Discharge Range: 15 - 21 ft. / 4.6 - 6.4 m

Operating Temperature Range:
-65°F to 120°F / -54°C to 49°C

Operating Pressure: 195 psi

ORDERING INFORMATION

20 LB Standard Dry Chemical Fire Extinguisher with Wall Hook-

Part No. 12220

Note: For Coast Guard Approval, you must also order the Model 811 Vehicle Bracket, P/N 700229

Refer to the Buckeye Spare Parts List for replacement parts