

# **CAJUN CUSTOM COOKERS LLC.**

## **NORTHWOODS EDITION REVERSE FLOW SMOKERS.**

Models: Tasso Northwoods Edition Series 48 – Series 60 – Series 72

Lil-Cajun Northwoods Edition Series 36 – Series 48 – Series 60

Cattleman Northwoods Edition Series 48 – Series – 60 – Series 72

## **STANDARD FEATURES**

- Available in 20" Diameter X 36", 48", 60" 24" Diameter X 48", 60", 72" 30" Diameter X 48", 60", 72".
- Outside of cook chamber, Inner fire box wall, outer fire box wall are made of ¼" thick 304 stainless steel, cook rack rails and supports are made of 1/8" thick 304 stainless steel, cook surface is made of 316 stainless steel and is available in multiple patterns.
- Reinforced dual ¼" thick wall fire box for reliable and safe insulating factor.
- 1/8" thick 304 stainless steel air dampers.
- Serviceable NSF certified door seals.
- Cook top on fire box made of 304 stainless steel.
- 1" ¼ turn stainless steel grease drain
- Digital/Analog Thermometers
- Pyro Ceram fire view window.
- Limited Lifetime warranty on main structure, welds, dampers, and latches.
- 1 year warranty on door seals and trailer components.
- Lock out tag out door locks.
- Auto locking cook door.
- Door latch locks for locking cook and fire box doors while in transport.

**EXTERIOR FINISH:** COOK CHAMBER AND FIRE BOX ARE MADE OF ¼" THICK 304 STAINLESS STEEL WITH #3 FINISH. COOK SURFACE IN MADE OF 316 STAINLESS STEEL WITH #4 FINISH. STRUCTURE IS WELDED INSIDE AND FOR EASY SANITIZING.

**NORTHWOODS REVERSE FLOW SMOKER:** AVAILABLE IN 20" DIAMETER X 36", 48", & 60" 24" DIAMETER X 48", 60", 72". 30" DIAMETER X 48", 60", & 72". LP CONVERSION KIT (80,000 BTU'S) W/CAST IRON BURNER AVAILABLE, 4 REMOVABLE LASER CUT COOKING GRATES.

**GAS HEAT CONTROL SYSTEM:** SYSTEM USES ONE ROUND CAST IRON BURNER THAT IS CONTROLLED BY A MANUAL GAS CONTROL VALVE WITH STANDARD PORTABLE LP TANK CONNECTOR. USES ELECTRONIC SPARK IGNITION POWERED BY ONE AA BATTERY.

**UNIVERSAL MOUNTING:** TRAILER FOR PORTABLE USE AND STATIONARY FRAME AVAILABLE.

**FIRE VIEW WINDOW:** MADE FROM ¼" THICK PYRO CERAMIC MATERIAL






# CAJUN CUSTOM COOKERS LLC.



## Safety Notice

This equipment is intended for commercial use only.  
 Smoker must be used in a safe non combustible area.  
 Never leave a wood/coal fire unattended. DO NOT FILL FIRE BOX MORE THAN 1/3 FULL WITH SOLID FUELS. Do not use lighter fluids or other accelerants to light solid fuels. Use propane torch or kindling to ignite solid fuels. Always drain grease when completing every 12 hours of cooking.



Model	Cook Surface weight capacity	Total sq inches of cook surface
Lil-Cajun series 36 Northwoods	100 LBS	960 sq in
Lil-Cajun series 48 Northwoods	150 LBS	1,320 sq in
Lil-Cajun series 60 Northwoods	200 LBS	1,680 sq in
Tasso series 48 Northwoods	225 LBS	1,760 sq in
Tasso series 60 Northwoods	275 LBS	2,240 sq in
Tasso series 72 Northwoods	325 LBS	2,720 sq in
Cattleman series 48 Northwoods	275 LBS	2,200 sq in
Cattleman series 60 Northwoods	350 LBS	2,800 sq in
Cattleman series 72 Northwoods	425 LBS	3,400 sq in

Model	Width	burners	Depth	Height	weight
Tasso series 48 Northwoods	66"	0/1	28"	60"	750 LBS
Tasso series 60 Northwoods	78"	0/1	28"	60"	825 LBS
Tasso series 72 Northwoods	90"	0/1	28"	60"	900 LBS
Lil-Cajun series 36 Northwoods	52"	0/1	24"	54"	550 LBS
Lil-Cajun series 48 Northwoods	64"	0/1	24"	54"	600 LBS
Lil-Cajun series 60 Northwoods	76"	0/1	24"	54"	650 LBS
Cattleman series 48 Northwoods	72"	0/1	34"	66"	1000 LBS
Cattleman series 60 Northwoods	84"	0/1/2	34"	66"	1150 LBS
Cattleman series 72 Northwoods	96"	0/1/2	34"	66"	1,300

# **CAJUN CUSTOM COOKERS LLC.**

## **Utility Information**

Wood/Coal use. DO NOT use starter fluids to ignite woos/coal. A torch is recommended to ignite these solids fuels. DOT NOT FILL FIRE BOX MORE THAN 1/3 OF INTERNAL FIRE BOX SPACE with solid fuels such as wood/coal.

Natural Gas/Liquid Propane: Portable units have ½" diameter line that is 3' long. A inline manual adjustable regulator with standard LP tank fitting is supplied.

Natural gas system: Minimum gas supply pressure is 7" W.C. Minimum pressure of 11" W.C. for propane. All gas systems require a regulated gas supply. Regulator is included. If a flexible connection hose is used it must be no smaller than ½" diameter line and connector must comply with ANSI Z21.69 providing restraint to prevent strain on the gas line.

Model	Natural Gas	Liquid Propane
Lil-Cajun series 36	80,000 BTU	80,000 BTU
Lil-Cajun series 48	80,000 BTU	80,000 BTU
Lil-Cajun series 60	80,000 BTU	80,000 BTU
Tasso series 48	80,000 BTU	80,000 BTU
Tasso series 60	80,000 BTU	80,000 BTU
Tasso series 72	80,000 BTU	80,000 BTU
Cattleman series 48	80,000 BTU	80,000 BTU
Cattleman series 60	160,000 BTU	160,000 BTU
Cattleman series 72	160,000 BTU	160,000 BTU

## **Options and accessories**

- |   |   |
|---|---|
| <ul style="list-style-type: none"><li>○ LP Burner</li><li>○ NG Burner</li><li>○ Laser cut fish cook surface</li><li>○ Laser cut vegetable cook surface</li><li>○ Laser cut griddle cook surface</li><li>○ Expanded stainless steel cook surface</li><li>○ Stainless steel pizza rack in fire box</li><li>○ 110v AC WIFI damper/temp control</li></ul> | <ul style="list-style-type: none"><li>○ Trailer</li><li>○ Push cart</li><li>○ Stationary frame</li><li>○ Wood storage compartment</li><li>○ Tool storage</li><li>○ Hand wash station</li><li>○ Umbrella canopy</li><li>○ Trailer brakes</li></ul> |
|---|---|