



Profit from the Eagle Advantage®

# Specification Sheet

## Short Form Specifications

Eagle Stem Caster, model \_\_\_\_\_. For use with 1"-diameter posts. Resilient or polyurethane tread. Casters with zinc, stainless steel, and polymer boot available. For electronic handling, conductive casters available. Donut bumper included with all stem casters. Swivel casters have a temperature rating of -15°F (-26°C). Note: These stem casters cannot be used with Master Trak® Shelving.

Item No.: \_\_\_\_\_  
 Project No.: \_\_\_\_\_  
 S.I.S. No.: \_\_\_\_\_

## Stem Casters

### MODELS:

- CSS3-175
- CSS5P-\*
- CSPB5-300
- A201009
- CSB3-175
- CSB5P-\*
- CPSS5PS-\*
- A204795
- CSS4-125
- CSR5P-\*
- CPBS5PS-\*
- A207562
- CSS5\*
- CSS5PS-\*
- A201706
- A200019
- CSB5\*
- CSB5PS-\*
- A201007
- A213261
- CSR5\*
- CSR5PS-\*
- A201008

\* See charts for complete model numbers.

Catalog Specification Sheet No. EG01.05A

Stem Casters



swivel caster with resilient tread

### Casters with Resilient Tread

type	EAGLEbrite® zinc model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	CSS3-175	175	79.4	3"	76	1"	25	1.1	0.5
w/brake	CSB3-175	175	79.4	3"	76	1"	25	1.1	0.5
swivel	CSS4-125	125	56.7	4"	102	1"	25	1.1	0.5
swivel	CSS5-300	300	136.1	5"	127	1 1/4"	32	2.5	1.2
w/brake	CSB5-300	300	136.1	5"	127	1 1/4"	32	2.8	1.3
rigid ▼	CSR5-300	300	136.1	5"	127	1 1/4"	32	3.5	1.6



(nickel-plated) caster with polyurethane tread

### Casters with Polyurethane Tread

Also available: Eaglebrite® zinc caster with step-pedal brake. Model #CSPB5-300

type	nickel-plated model #	stainless steel model #	capacity		wheel diameter		wheel face		weight	
			lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	CSS5P-300	CSS5PS-300	300	136.1	5"	127	1 1/4"	32	2.5	1.1
w/brake	CSB5P-300	CSB5PS-300	300	136.1	5"	127	1 1/4"	32	2.8	1.3
rigid ▼	CSR5P-300	CSR5PS-300	300	136.1	5"	127	1 1/4"	32	3.5	1.6



conductive caster

### Conductive Casters

For electronic handling only. Meets Federal Specification #FF-C-88C standards.

type	EAGLEbrite® zinc model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	CSS5-CC	200	90.7	5"	127	1 1/4"	32	2.5	1.1
w/brake	CSB5-CC	200	90.7	5"	127	1 1/4"	32	2.8	1.3
rigid ▼	CSR5-CC	200	90.7	5"	127	1 1/4"	32	3.5	1.6

▼ See back page for optional Channel Frames available for use with rigid casters.

**EAGLE GROUP**  
 100 Industrial Boulevard, Clayton, DE 19938-8903 USA  
 Phone: 302-653-3000 • 800-441-8440  
 Fax: 302-653-2065  
 www.eaglegrp.com • www.eaglehmc.com



For custom configuration or fabrication needs, contact our SpecFAB® Division.  
 Phone: 302-653-3000 • Fax: 302-653-2065 • e-mail: quotes@eaglegrp.com

EG01.05A Rev. 02/26

Spec sheets available for viewing, printing or downloading from our online literature library at our websites



Item No.: \_\_\_\_\_  
 Project No.: \_\_\_\_\_  
 S.I.S. No.: \_\_\_\_\_

## Stem Casters



cart-washable  
caster

### Cart-Washable Casters

Features stainless steel boot, swivel stem, sealed precision bearings, and polyurethane wheel.

type	stainless steel model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	<b>CSS5WPS-300</b>	300	136.1	5"	127	1 1/4"	32	2.0	0.9
w/brake	<b>CSB5WPS-300</b>	300	136.1	5"	127	1 1/4"	32	2.0	0.9




polymer caster

### Polymer Casters

With polyurethane tread.

type	model #	type of bearing	capacity		wheel diameter		wheel face		weight	
			lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	<b>CPSS5-250</b>	delrin	250	113.4	5"	127	1 1/4"	32	2.0	0.9
w/brake	<b>CPSB5-250</b>	delrin	250	113.4	5"	127	1 1/4"	32	2.0	0.9



channel frame

### Channel Frames—for Rigid Stem Casters

Please note that shelf width must be known when ordering rigid stem casters in order to ship appropriate channel frame to lock rigid casters.

model #	shelf width		weight	
	in.	mm	lbs.	kg
<b>A201706</b>	14"	356	1.5	0.7
<b>A201007</b>	18"	457	2.0	0.9
<b>A201008</b>	21"	533	2.5	1.1
<b>A201009</b>	24"	610	2.8	1.3
<b>A204795</b>	30"	762	3.5	1.6
<b>A207562</b>	36"	914	4.0	1.8



donut bumper  
#A200019

### Donut Bumpers—for all Stem Casters

description	model #
3 1/2" (89mm) diameter	<b>A200019</b>
5" (127mm) diameter, with swivel center	<b>A213261</b>

#### EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 or 800-441-8440 • Fax: 302-653-2065

www.eaglegrp.com • www.eaglehmc.com

Printed in U.S.A.  
©2026 by Eagle Group

Rev. 02/26

Spec sheets available for viewing, printing or downloading from our online literature library at [www.eaglegrp.com](http://www.eaglegrp.com)

Although every attempt has been made to ensure the accuracy of the information provided, we cannot be held responsible for typographical or printing errors. Information and specifications are subject to change without notice. Please confirm at time of order.