

BACK BAR EQUIPMENT

MODEL: BC24N-SS
Natural Refrigerant R-290 Model

24” Bottle Cooler (38’F-41’F)

Stainless steel exterior with all stainless steel countertop and slide lids heavy duty galvanized interior.



Options and Accessories

(upcharge and lead times may apply)	
Stainless steel interior	Expansion Valve System
Additional wire bin dividers	Casters
Lid Lock	Adjustable legs

Project Name:

Model Specified:

Location:

Item No:

Quantity:

AIA #:

SIS #:

Standard Model Features

REFRIGERATION SYSTEM

Natural Refrigerant R-290 Model

Performance rated **front breathing** refrigeration system

Automatic, energy saving, non-electric condensate evaporator

Full length, extra large coil

Easily accessible and serviceable slide out condensing unit

CABINET ARCHITECTURE

High density, non-CFC polyurethane foamed-in-place insulation

Heavy duty, epoxy coated, adjustable steel wire storage bin dividers

MODEL FEATURES

Heavy duty cap opener with extra capacity, removable cap catcher

Easily accessible, front mounted cleanout drainage hose

Electronic controller with digital display

APPROVAL:

Model Specifications

DIMENSIONAL DATA

Net Capacity (cubic feet)	4.8 (136 cu l)
12 oz. Bottle Capacity (# cases)	4.5
12 oz. Can Capacity (# cases)	7.5
Width, Overall (inches)	24 (610 mm)
Depth, Overall (inches) (including bumpers & cap catcher)	28.13 (715 mm)
Height, Overall (inches)	33.50 (851 mm)
Number of Slide Lids	1
Number of Bin Dividers	2

REFRIGERANT DATA

Condensing Unit Size (H.P.)	1/5
Capacity (BTU per hour)*	1800

ELECTRICAL DATA

Voltage (International)	115-60-1 (220-50-1)
Feed Wires (including ground)	3
Total Amps (International)	2.2 ()
10 ft. Cord/Plug [attached] (International)	Yes (No)

SHIPPING DATA

Weight - (pounds)	219 (99 kg)
Height - Crated (inches)	40.25 (1022 mm)
Width - Crated (inches)	33 (838 mm)
Depth - Crated (inches)	30.25 (768 mm)

* Rating @ +20°F evaporator, 90°F ambient

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.

Equipped with one NEMA-5-15P Plug (varies by country)

Continental

Refrigerator

Due to our continued efforts in developing innovative products, specifications subject to change without notice.

ETL

US

Intertek

NSF

Proudly Designed and Assembled in the USA

Toll-Free: 800-523-7138

Phone: 215-244-1400

Fax: 215-244-9579

539 Dunksferry Road

Bensalem, PA 19020

www.continentalrefrigerator.com

Model Plan Views

FRONT VIEW

SIDE VIEW

IMPORTANT: Model is completely front breathing and intakes and exhausts air through the front grill. A clearance of 1” on the back and 3” on the sides is recommended.

REVISED: 8/30/23