

FEDERAL INDUSTRIES

A Standex Company 215 Federal Avenue Belleville, WI 53508-9201

Phone: 800-356-4206 Fax: 608-424-3234 Email: geninfo@federaling

Email: geninfo@federalind.com Website: www.federalind.com

Project Name:	AIA#
Item #:	
Model #: Qty:	SIS#
Approval:	

HYBRID MERCHANDISER

SERVICE NON-REFRIGERATED OVER SELF-SERVE REFRIGERATED

MODEL	DIMENSIONS (Includes End Panels)
- cpacae/pccace	, · · · · · · · · · · · · · · · · · · ·
□ CD3628/RSS3SC	36.25x 39 x 69.75 (in)
	921 x 991 x 1772 (mm)
□ CD4828/RSS4SC	48 x 39 x 69.75 (in)
	1219 x 991 x 1772 (mm)
□ (2)CD3628/RSS6SC	72 x 39 x 69.75 (in)
	1829 x 991 x 1772 (mm)

Display more product and serve more customers with presentation and value in mind.



OPTIONAL ACCESSORIES

For Top Display

- ☐ Glass Shelves
- ☐ Reflective Ends
- □ Reflective Rear Doors

For Self-Serve Refrigerated Base

- ☐ Energy Saving Night Curtain
- ☐ Silver Trim
- ☐ Special Base Finish
- ☐ Mirrored Interior Ends
- ☐ Security Night Cover
- ☐ Stainless Steel Steps in Lieu of Metal Shelves
- ☐ Reflective End Glass

SELF-SERVE NON-REFRIGERATED OVER SELF-SERVE REFRIGERATED

MODEL	DIMENSIONS (Includes End Panels)
□ CD3628SS/RSS3SC	36.25 x 39 x 69.75 (in)
	921 x 991 x 1772 (mm)
□ CD4828SS/RSS4SC	48 x 39 x 69.75 (in)
	1219 x 991 x 1772 (mm)
□ (2)CD3628SS/RSS6SC	72 x 39 x 69.75 (in)
	1829 x 991 x 1772 (mm)

STANDARD FEATURES

Refrigerated Self-Serve Bottom Display

- Black laminated exterior. Other finishes available.
- Black trim. Silver optional.
- Black interior, glass ends.
- Horizontal LED top and front light.
- Two tiers black metal shelves.
- Electronic temperature control maintains 38° to 40° case temperature. Note: Case temperature will vary if the air curtain is disrupted.
- Cord and plug. (Not available on RSS6SC.)
- Condensate evaporator (separate circuit required on model RSS6SC)
- R513a Refrigerant

Service or Self-Serve Non-Refrigerated Top Display

- Two tiers black wire shelves.
- Sliding rear doors.
- Black trim.
- Self-Serve has three hinged lift-up front doors.

Lighting

• LED top light and shelf lights.

Agency Approvals

- UL Safety and UL Sanitation Listed to NSF Type II conditions.
- DOE 2017 Compliant













AIA#

HYBRID MERCHANDISER

SIS#

Product Specifications


Intended Environment: Type I - Designed to operate in maximum ambient conditions of 75°F (24°C) and 55% relative humidity unless noted otherwise in system information below.

Zone	Intended Product To Be Displayed	Avg Prod Temp °F/°C
All	Packaged Refrigerated Products	38°F / (3.3°C)


DIMENSION: xx"/(mm)

DIMENSION TOLERANCE +/- 0.19 (4.8)

SERVICE NON-REFRIGERATED OVER SELF-SERVE REFRIGERATED



SELF-SERVE NON-REFRIGERATED OVER SELF-SERVE REFRIGERATED



MODEL	DIMENSIONS			SHIPPING WHT		BOTTOM DISPLAY	TOP DISPLAY			
	L	D	н	UNITS	LBS	KILO	120/60/1 (NEMA 5-20P)	120/60/1 (NEMA 5-15P)		
CD3628/RSS3SC	36.25	39	69.75	in.	847	847 384	1/3 HP - 14.8 AMPS	1.5 AMPS		
	921	991	1772	mm.						
CD4828/RSS4SC	48	39	69.75	in.	1,010	1,010 45	450 1.	1/2 HP - 16.0 AMPS	1.5 AMPS	
	1219	991	1772	mm.			458			
(2)CD3628/RSS6SC*	72	39	69.75	in.	1,500	1,500 680	600	2/4115 45 0 4145	(2) 4 5 44406	
	1829	991	1772	mm.			3/4 HP - 16.0 AMPS	(2) 1.5 AMPS		
CD3628SS/RSS3SC	36.25	39	69.75	in.	790	790	700	358	1/3 HP - 14.8 AMPS	1.5 AMPS
	921	991	1772	mm.			338	1/3 FF - 14.8 AIVIP3	1.5 AIVIPS	
CD4828SS/RSS4SC	48	39	69.75	in.	900	900	000	900 408	1/2 16.0 AMDS	1.F. AMDC
	1219	991	1772	mm.			408	1/2 HP - 16.0 AMPS	1.5 AMPS	
(2)CD3628SS/RSS6SC*	72	39	69.75	in.	1,300	1,300		2/4 UD 46 0 414DC	(2) 4 5 44406	
	1829	991	1772	mm.			590	3/4 HP - 16.0 AMPS	(2) 1.5 AMPS	

- * On the RSS6SC a separate 120/60/1 15 AMP circuit is required for the condensate evaporator.
- If a GFCI circuit is required, a GFCI Breaker Must be used instead of GFCI recepticle.
- Refrigerated cases are designed to operate in a maximum of 75°F (24°C) ambient and 55% relative humidity.
- Due to continuing engineering improvements, specifications are subject to change without notice.a











FEDERAL INDUSTRIES A Standex Company

215 Federal Avenue Belleville, Wisconsin 53508-9201

Phone: 800-356-4206 **Fax:** 608-424-3234

Email: Geninfo@Federalind.com **Website:** Federalind.com