

# HP 19A Original LaserJet Imaging Drum (CF219A)

## Overview

**HP 19A LaserJet Imaging Drum, black, 12,000 pages[3]**



Count on consistent, impressive quality and performance, using Original HP imaging drums with JetIntelligence—designed to help protect your investment and help your printer work its best.

### Claim all the pages

Original HP imaging drums with JetIntelligence provide professional-quality results and are precisely tuned to match the powerful performance of your HP printer or MFP.

### Get peace of mind with anti-fraud protection

Don't be fooled by alternatives that mimic Original HP. Help ensure you're getting the quality you paid for.

### Print fast without sacrificing quality

Continue to count on consistent quality with Original HP imaging drums with JetIntelligence.

### Designed for reliable performance

Continue to count on consistent quality with imaging drums tuned to match the speed of your HP printer or MFP.

## Features



Designed to work the first time, every time<sup>[4]</sup>



Quality prints you can take pride in



The environmental choice.<sup>[5]</sup>



Better together. Better results.



Professional-quality pages



Dependable print gauge technology<sup>[1]</sup>

---

*[1] As compared with cartridge gauges for HP predecessor products.*

*[3] Approximate average yield based on ISO/IEC 19752. Actual yield varies considerably based on content of printed pages and other factors. For details see <http://www.hp.com/go/learnaboutsupplies>.*

*[4] See <http://www.hp.com/go/suppliesclaims>.*

*[5] HP Planet Partners Program availability varies. For details, see <http://www.hp.com/recycle>. On recycled materials in cartridges, see <http://www.hp.com/go/recycledcontent>.*

## Specifications

<b>Color(s) of printing supplies</b>	Black
<b>Print Technology</b>	Laser
<b>Supply type</b>	Imaging Drums
<b>Operating temperature range</b>	15 to 32.5°C
<b>Storage temperature range</b>	-20 to 40°C
<b>Operating humidity range</b>	20 to 80% RH
<b>Non-Operating Humidity Range</b>	0 to 95% RH
<b>Print Resolution Technologies</b>	JetIntelligence
<b>Compatibility</b>	HP LaserJet Pro M102 Printers, HP LaserJet Pro M104 Printers, HP LaserJet Pro MFP M130, HP LaserJet Pro MFP M132
<b>Product count per unit</b>	1
<b>Quantity per pallet</b>	319
<b>Quantity per European pallet</b>	230
<b>Cartons per pallet</b>	319
<b>UPC number</b>	889894797421
<b>Minimum dimensions (W x D x H)</b>	365 x 97 x 102 mm
<b>Minimum dimensions (W x D x H)</b>	14.37 x 3.82 x 4.02 in
<b>Package dimensions (W x D x H)</b>	365 x 97 x 102 mm
<b>Package dimensions (W x D x H)</b>	14.37 x 3.82 x 4.02 in
<b>Pallet dimensions (W x D x H)</b>	1100 x 961 x 1266 mm
<b>Pallet dimensions</b>	43.3 x 37.8 x 49.8 in
<b>Package weight</b>	~0.42 kg
<b>Package weight</b>	~0.93 lb
<b>Pallet weight</b>	154.8 kg
<b>Pallet weight</b>	340.5 lb
<b>Page Yield</b>	12000
<b>Page yield (black and white)</b>	~12,000 pages
<b>What's in the box</b>	Imaging drum; Recycling guide
<b>Manufacturer Warranty</b>	HP's Premium Protection Warranty. This HP product is warranted to be free from defects in materials and workmanship.

## Additional specifications

<b>Cartons per layer</b>	29
<b>Cartridge Colors</b>	Black
<b>Compatibility 01</b>	HP LaserJet Pro M102, M130
<b>Compatibility headline</b>	HP 19 toner cartridges work with:
<b>Count of layers in pallet</b>	11
<b>Country of origin</b>	Made in Vietnam
<b>European pallet dimensions (W x D x H)</b>	1100 x 763 x 1169 mm
<b>Master or single cartons per layer (European pallet)</b>	23
<b>Operating temperature range</b>	59 to 90.5°F
<b>Package count</b>	1
<b>Page yield (black)</b>	1 Black (~12,000 pages)
<b>Page yield footnote</b>	Approximate average yield based on ISO/IEC 19752. Actual yield varies considerably based on content of printed pages and other factors. For details see <a href="http://www.hp.com/go/learnaboutsupplies">http://www.hp.com/go/learnaboutsupplies</a> .
<b>Pallet weight</b>	117.3 kg
<b>Print technology</b>	Laser
<b>Product subgroup</b>	Fuser/Maintenance Kits
<b>Segment (filter)</b>	JetIntelligence
<b>Selectability</b>	19A
<b>Stacking number for carton</b>	44
<b>Storage temperature range</b>	-4 to 104°F
<b>UNSPSC code</b>	44103109

**Warranty**

HP's Premium Protection Warranty. This HP product is warranted to be free from defects in materials and workmanship. This warranty does not apply to print cartridges that (a) have been refilled, refurbished, remanufactured or tampered with in any way, (b) experience problems resulting from misuse, improper storage, or operation outside of the published environmental specifications for the printer product or (c) exhibit wear from ordinary use. To obtain warranty service, please return the product to place of purchase (with a written description of the problem and print samples) or contact HP customer support. At HP's option, HP will either replace products that prove to be defective or refund your purchase price. TO THE EXTENT ALLOWED BY LOCAL LAW, THE ABOVE WARRANTY IS EXCLUSIVE AND NO OTHER WARRANTY OR CONDITION, WHETHER WRITTEN OR ORAL, IS EXPRESSED OR IMPLIED AND HP SPECIFICALLY DISCLAIMS ANY IMPLIED WARRANTIES OR CONDITIONS OF MERCHANTABILITY, SATISFACTORY QUALITY, AND FITNESS FOR A PARTICULAR PURPOSE. TO THE EXTENT ALLOWED BY LOCAL LAW, IN NO EVENT WILL HP OR ITS SUPPLIERS BE LIABLE FOR DIRECT, SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFIT OR DATA), OR OTHER DAMAGE, WHETHER BASED IN CONTRACT, TORT, OR OTHERWISE. THE WARRANTY TERMS CONTAINED IN THIS STATEMENT, EXCEPT TO THE EXTENT LAWFULLY PERMITTED, DO NOT EXCLUDE, RESTRICT OR MODIFY AND ARE IN ADDITION TO THE MANDATORY STATUTORY RIGHTS APPLICABLE TO THE SALE OF THIS PRODUCT TO YOU.

**Weight**

~0.43 lb

**Weight**

~0.2 kg

## Disclaimer — Copyright

© Copyright 2022 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (us-en) – Nov 07, 2022 3:10 PM UTC+0000