



# **APPLICATIONS**







Lodging



Packaged Ice

# **SPECIFICATIONS**

Daily Ice Production<sup>[1]</sup> per 24hrs



## CNM0630 SERIES

# **FEATURES**



#### **Unique Dual Exhaust**

All air-cooled models allow for top or side hot-air discharge for increased installation flexibility



#### **Environmentally Responsible**

- Exceeds 2018 Department of Energy regulations
- 20% more efficient than previous Nordic models



#### Sanitation

- Automated cleaning cycle
- Dishwasher safe, food zone components
- Easy to clean structural foam base is rust free Common



#### Components

- Reservoir, water pump, board, float, fan
- Easy-access, forward facing evaporators on all models
- Less inventory required for service providers
- Quicker response times

				,					
Model Number	Condenser Type	70°F Air / 50°F Water	90°F Air / 70°F Water	Electrical (V/Hz/Ph)	Energy <sup>[#]</sup> Usage	Min Circuit	Fuse Size	Water Usage Potable <sup>[2]</sup>	Shipping Weight
CNIN40C20A*CA	Λ:-	600 lbs	455 lbs	208-	E C LAMIL	9.2	15.0	10 C col	160 lbs
CNM0630A*6A	Air	272 kg	206 kg	230/60/1	5.6 kWH	Amps	amps	18.6 gal	73 kg
CNIN 40C20D*CA	D	615 lbs	535 lbs	208-	E 2 JA441	10.0	15.0	19.0 gal	160 lbs
CNM0630R*6A	Remote	279 kg	243 kg	230/60/1	5.3 kWH	Amps	amps		73 kg
CNM0630A*5A	Air	585 lbs	450 lbs	220		10.1 16.0 Amps amps	16.0	20.0	160 lbs
		265 kg	204 kg	240/50/1			20.0 gal	73 kg	

<sup>\*</sup> Replace \* with "F" for full cube and "H" for half cube

- Daily production assumes half cube models.
- Water usage in gallons per 100 lbs of ice produced at 90°F Air / 70°F Water.
- kWH Used per 100 lbs of ice produced at 90°F Air / 70°F Water.

#### **DISPENSER ADAPTER KITS**

Adapter Kit	Adapter Kit Qty	Bin Thermostat	Bin Stat Qty
629096683TE	1	Included in Adapter Kit	N/A
629096683TE	1	Included in Adapter Kit	N/A
629096687TE	1	Included in Adapter Kit	N/A
629096687TE	1	Included in Adapter Kit	N/A
Not Required	1	631500109X	1
629096792TE	1	Included in Adapter Kit	N/A
629096792TE	1	Included in Adapter Kit	N/A
629096793TE	1	Included in Adapter Kit	N/A
	629096683TE 629096683TE 629096687TE 629096687TE Not Required 629096792TE 629096792TE	Adapter Kit Qty  629096683TE	Adapter Kit         Qty         Bin Thermostat           629096683TE         1         Included in Adapter Kit           629096683TE         1         Included in Adapter Kit           629096687TE         1         Included in Adapter Kit           629096687TE         1         Included in Adapter Kit           Not Required         1         631500109X           629096792TE         1         Included in Adapter Kit           629096792TE         1         Included in Adapter Kit


### **OTHER ACCESSORIES**


Bin Model	Adapter Kit		
B530AP	Not Required		

<b>Hotel Dispenser</b>	Adapter Kit		
CHD30P1	Not Required		


Remote Condenser					
RCN1061	Required for CNM0630R				
RT25	25' Line Set				
RT50	50' Line Set				
RT75	75' Line Set				
620060081	Optional Grill Kit Field Installed				

# **SCHEMATICS**





A. Ice maker potable water in	3/8" FPT.
B. Ice maker water out	1/2" FPT.
C. Hole for electrical connection	7/8"
D. Electrical connection junction box	7/8"
E. Condenser water in (water cooled unit)	3/8"
E. Discharge line (remote cooled only)	1/2" male quick connect
F. Condenser water out (water cooled unit)	1/2"
G. Liquid line (remote cooled only)	3/8" male quick connect



#### **OPERATING REQUIREMENTS**

Ambient Air Temperature	50°F 10°C	100°F 38°C
Water Temperature	40°F 4°C	100°F 38°C
Water Pressure	20 psig 1.4 bar	60 psig 5.5 bar

#### CROSS REFERNECE TO PRIOR MODELS

Legacy Nordic Model	Equivalent Nordic Elite Model
CCM0630AF21	CNM0630AF6A
CCM0630AH21	CNM0630AH6A
CCM0630RF21	CNM0630RF6A
CCM0630RH21	CNM0630RH6A
CCM0630AF51	CNM0630AF5A
CCM0630AH51	CNM0630AH5A

#### WARRANTY

- 3 years parts & limited labor
- 5 years compressor & evaporator parts
- See website for warranty details

#### **ADDITIONAL SPECS**

Full Cube (W x D x H)	Half Cube (W x D x H)		
.88 x .88 x .88 in	.38 x .88 x .88 in		
2.2 x 2.2 x 2.2 cm	1.0 x 2.2 x 2.2 cm		

Water Usage <sup>[2]</sup> (Water cooled condenser only)	180.0 gal			
Remote Condenser	RCN1061			
Heat Rejection	8,600 BTU/hr			
Dimensions (W x D x H)	30 x 24 x 21 in	77 x 62 x 54 cm		

[2] Water usage in gallons per 100 lbs of ice produced at 90°F Air / 70°F Water.

Power cord wires	3 including ground					
Refrigerant	R404a					
Listings	c UL us	NSF	< €	(U <sub>L</sub> )	# 1997 #68 # # 2231 # 228/14 STAT	
	agion <sup>*</sup> Nature's antimicrobial	0	BPA Free			



IN THE U.S.A. Ph: 800.238.3600 Fax: 800.258.0255 OUTSIDE THE U.S.A Ph: 763.488.8200 Email: webmaster@cornelius.com

101 Broadway Street West Osseo, MN 55369 www.cornelius.com