

Item#:		
Quantity:		
Model #:	CC-LTC-	BR
Project #:		

## Insulated Ice-Cooled Bottle Rails

#### Model #: CC-LTC-4BR

(Bottles not included, by others)

See next page for a complete list of available models.

### **Standard Features:**

- Ice-cooled, non-electrical dependency allows it to be placed in the most convenient locations
- Includes Steril-Sil #S-500 perforated cylinders
- Cylinder holes allow maximum air-flow and direct contact of cool air with bottles for the most efficient temperature holding
- Foamed in place insulated base holds temperature for hours on a single ice charge
- Compact design takes up little counter-top space
- S-500 cylinders hold standard 3.5" diameter bottles (not included, by other)
- Rear lid is hinged for easy ice recharge
- Light weight and portable
- Includes non-marking feet
- All welded 304 stainless steel construction
- Made in the U.S.A.

#### **Product Specification:**

Steril-Sil model #CC-LTC-BR Insulated Ice-Cooled Bottle Rail. All 304 series stainless steel construction inside and out. Foamed in place base. Rear hinged lid for ice recharge. Includes S-500 cylinders for maximum cooling air-flow. Designed for use with standard 3 1/2" diameter bottles. (Bottle by other.) Made in the U.S.A.

#### Steril-Sil, LLC

1050 Commonwealth Avenue Boston, MA 02215 Phone: 800-784-5537 Fax: 617-739-5063 Email: sales@sterilsil.com www.sterilsil.com

Notes:			

# Insulated Ice-Cooled Bottle Rails



## Insulated Ice-Cooled Bottle Rails

Includes #S-500 perforated cylinders, bottles by others

Model	Description	Bottle Capacity	Length	Width	Height	Ship #
CC-LTC-3BR	3-hole insulated countertop dispenser complete with S-500 cylinders for maximum air-flow	3	16"	8 ¾"	7 ¾"	13 lbs.
CC-LTC-4BR	4-hole insulated countertop dispenser complete with S-500 cylinders for maximum air-flow	4	20 ½"	8 ¾"	7 ¾"	17 lbs.
CC-LTC-5BR	5-hole insulated countertop dispenser complete with S-500 cylinders for maximum air-flow	5	25″	8 ¾"	7 ¾"	21 lbs.
CC-LTC-6BR	6-hole insulated countertop dispenser complete with S-500 cylinders for maximum air-flow	6	30"	8 ¾"	7 ¾"	25 lbs.



See the Condiment Accessories page for additional options and details