

# BASE MODEL SANDWICH UNIT

## Model: RA43N9M-D

Natural Refrigerant R-290 Model

### 43" Mighty Top Sandwich Unit Refrigerator with Drawers - 9 Pans

Heavy gauge #300 series stainless steel top, stainless steel front and end panels, galvanized steel rear and grills and aluminum interior.



#### Options and Accessories

(upcharge and lead times may apply)

|                                |                                                           |
|--------------------------------|-----------------------------------------------------------|
| Stainless steel interior       | Rear-mounted cutting board                                |
| Stainless steel back           | Condensing unit left (standard on right)                  |
| Overshelves (single or double) | Drawer in lieu of door section above the condensing unit* |
| Vision panel lid               | Drawer/door locks                                         |
| Flat insulated night cover     | Adjustable legs                                           |
| Composite cutting board        | Front breathing                                           |

Consult factory for other model configurations, options and accessories.

\*Drawer section above condensing unit holds (1) 12 x 20 x 6 pan.

**Continental**  
Refrigerator

Toll-Free: 800-523-7138  
Phone: 215-244-1400  
Fax: 215-244-9579

539 Dunksferry Road  
Bensalem, PA 19020  
[www.continentalrefrigerator.com](http://www.continentalrefrigerator.com)

Project Name:

Model Specified:

Location:

Item No:

Quantity:

AIA #:

SIS #:

#### Standard Model Features

##### REFRIGERATION SYSTEM

Performance-rated refrigeration system

Natural, environmentally-safe, high-efficiency R-290 refrigerant<sup>1</sup>

Unique forced air design utilizes fans (approx. every 12") across the entire back of unit for even distribution of cold

Automatic, hot gas condensate evaporator

Non-corrosive, plasticized fin evaporator coil

Easily serviceable, slide-out condensing unit

Expansion valve system

##### CABINET ARCHITECTURE

2" non-CFC polyurethane foam insulation

Smooth, polished chrome drawer/door handles

Spring loaded, self closing door (over condensing unit)

Magnetic snap-in drawer/door gaskets

Stainless steel roll-out drawers

10" deep, full length nylon cutting board

Insulated lid

5" casters

##### MODEL FEATURES

(9) 1/6 size recessed pans, 4" deep

Electronic controller w/digital display & hi-low alarm

Refrigerated section w/door above the condensing unit

Field rehingeable door (over condensing unit)

<sup>1</sup> R-290 refrigerant meets all federal and state regulatory requirements.

**NOTE:** Models come standard with a door above the condensing unit. A drawer above the condensing unit is an option.

APPROVAL:

## Model Specifications

### DIMENSIONAL DATA

|                                                   |                 |
|---------------------------------------------------|-----------------|
| Net Capacity (cu. ft.)                            | 12 (340 cu l)   |
| 1/6 Size Pans (4" deep)                           | 9               |
| Width, Overall (in.)                              | 43 (1092 mm)    |
| Depth, Overall (in.)<br>(incl. handles & bumpers) | 37 (940 mm)     |
| Depth, Cutting Board (in.)                        | 10 (254 mm)     |
| Height, Overall (in.) (incl. 5" casters)          | 42 (1067 mm)    |
| No. of Drawers                                    | 2               |
| No. of Half Doors                                 | 1               |
| Interior Depth (in.) (above condenser)            | 30 (762 mm)     |
| Interior Height (in.) (above condenser)           | 12 1/2 (318 mm) |
| Interior Width (in.) (above condenser)            | 17 (432 mm)     |

### REFRIGERANT DATA

|                             |      |
|-----------------------------|------|
| Condensing Unit Size (H.P.) | 1/4  |
| Capacity (BTU/Hr)*          | 2000 |

### ELECTRICAL DATA

|                                     |                     |
|-------------------------------------|---------------------|
| Voltage (int'l)                     | 115/60/1 (220/50/1) |
| Fans                                | 2                   |
| Total Amps (int'l)                  | 5.1 (4.0)           |
| 10 ft. Cord/Plug [attached] (int'l) | Yes (No)            |

### SHIPPING DATA

|                       |                  |
|-----------------------|------------------|
| Weight (lbs.)         | 350 (159 kg)     |
| Height - Crated (in.) | 43 3/4 (1111 mm) |
| Width - Crated (in.)  | 45 (1143 mm)     |
| Depth - Crated (in.)  | 47 (1194 mm)     |

### DRAWER PAN CONFIGURATIONS

**Two Tier:** (1) 12 x 20 x 6 pan & (3) 1/6 x 6 pans (top)  
(2) 12 x 20 x 6 pans (bottom). Three tier not available.

\* Rating @ +25°F evaporator, 90°F ambient

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Equipped with one NEMA-5-15P Plug  
(varies by country)

**Continental**  
Refrigerator

Toll-Free: 800-523-7138  
Phone: 215-244-1400  
Fax: 215-244-9579

539 Dunkserry Road  
Bensalem, PA 19020  
[www.continentalrefrigerator.com](http://www.continentalrefrigerator.com)

Due to our continued efforts in developing innovative products, specifications subject to change without notice.



MADE IN THE U.S.A.

© Copyright 2020. Continental Refrigerator.  
A Division of National Refrigeration & Air Conditioning Products, Inc.

## Model Plan Views

