### BASE MODEL SANDWICH UNIT

### Model: RA60N8

Natural Refrigerant R-290 Model

# 60" Standard Top Sandwich Unit Refrigerator with Solid Doors - 8 Pans

Heavy gauge #300 series stainless steel top, stainless steel front and end panels, galvanized steel rear and grills and aluminum interior.



#### **Options and Accessories**

(upcharge and lead times may apply)

Stainless steel interior	Crumb catcher
Stainless steel back	Composite cutting board
Overshelves (single or double)	Rear-mounted cutting board
Add'l epoxy-coated steel shelves	Condensing unit left (standard on right)
Stainless steel shelves	Drawer in lieu of door section above the condensing unit*
Pan slides (larger section only)	Door locks
Vision panel lid	Adjustable legs
Flat insulated night cover	Front breathing

Consult factory for other model configurations, options and accessories.

<sup>\*</sup>Drawer section above condensing unit holds (1) 12 x 20 x 6 pan.



**Toll-Free: 800-523-7138** Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Project Name:	
Model Specified:	
Location:	
Item No:	Quantity:

AIA #: SIS #:

#### **Standard Model Features**

#### REFRIGERATION SYSTEM

Performance-rated refrigeration system

Natural, environmentally-safe, high-efficiency R-290 refrigerant<sup>1</sup>

Unique forced air design utilizes fans (approx. every 12") across the entire back of unit for even distribution of cold

Automatic, hot gas condensate evaporator

Non-corrosive, plasticized fin evaporator coil

Easily serviceable, slide-out condensing unit

Expansion valve system

#### **CABINET ARCHITECTURE**

2" non-CFC polyurethane foam insulation
Smooth, polished chrome door handles
Spring loaded, self closing doors
Magnetic snap-in door gaskets
Heavy-duty, epoxy-coated steel shelves
12" deep, full length nylon cutting board
Insulated lid
5" casters

#### **MODEL FEATURES**

(8) 1/6 size recessed pans, 4" deep
Electronic controller w/digital display & hi-low alarm
Refrigerated section w/door above the condensing unit
Field rehingeable doors

<sup>1</sup> R-290 refrigerant meets all federal and state regulatory requirements.

<u>NOTE</u>: Models come standard with a door above the condensing unit, a smaller width door (left section) and larger width door (center section). The option of having the doors located in the opposite sections <u>MUST</u> be indicated at the time of ordering. A drawer above the condensing unit is an option.

APPROVAL:

#### **Model Specifications**

DIMENSIONAL DATA	
Net Capacity (cu. ft.)	19 (538 cu I)
1/6 Size Pans (4" deep)	8
Width, Overall (in.)	60 (1524 mm)
Depth, Overall (in.) (incl. handles & bumpers)	37 (940 mm)

Depth, Cutting Board (in.) 12 (305 mm)
Height, Overall (in.) (incl. 5" casters) 42 (1067 mm)

 Shelf Area (sq. ft.)
 7.1 (.7 sq m)

 No. of Shelves
 4

 No. of Full Doors
 2

No. of Half Doors 1
Interior Depth (in.) 30 (762 mm)

Interior Height (in.) 26 (660 mm)

Interior Height (in.) (above condenser) 12 1/2 (318 mm)

Interior Width (in.) 56 (1422 mm)

#### **REFRIGERANT DATA**

Condensing Unit Size (H.P.) 1/3
Capacity (BTU/Hr)\* 2600

#### **ELECTRICAL DATA**

Voltage (int'l)	115/60/1 (220/50/1)
Fans	3
Total Amps (int'l)	7.0 (4.7)
10 ft. Cord/Plug [attached] (int'l)	Yes (No)
ALUBRIUS BATA	

#### **SHIPPING DATA**

Weight (lbs.)	420 (191 kg)
Height - Crated (in.)	43 3/4 (1111 mm)
Width - Crated (in.)	62 (1575 mm)
Depth - Crated (in.)	47 (1194 mm)

<sup>\*</sup> Rating @ +25°F evaporator, 90°F ambient

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.

Refrigerator



Equipped with one NEMA-5-15P Plug (varies by country)

## **Continental**°

**Toll-Free: 800-523-7138** Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.







© Copyright 2020. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

#### **Model Plan Views**





