

35160GMNRBNL

Cooking Performance Group G60-NG(CPG) 60" Gas Countertop Griddle with Manual Controls and 60", 2 Drawer Refrigerated Chef Base - 150,000 BTU



Item #: 35160GMNRBNL Qty: _____

Project: _____

Approval: _____ Date: _____

Features

- 5 independently-controlled 30,000 BTU burners with continuous pilot for instant ignition
- Removable waste tray and adjustable feet
- Heavy-duty, 3/4" thick steel griddle plate
- Field convertible to liquid propane; includes orifice for connection
- Digital display base uses 1/6 hp; 115V; environmentally friendly R290 refrigerant



Technical Data

Width	60 Inches
Depth	32 1/8 Inches
Height	42 9/16 Inches
Cooking Surface Width	60 Inches
Interior Width	48 1/4 Inches
Base Depth	32 1/8 Inches
Cooking Surface Depth	20 Inches
Interior Depth	27 9/16 Inches
Top Step Depth	60 Inches
Base Height	25 13/16 Inches

Certifications

ETL Sanitation 5-15P

3/4" Gas Connection

Field Convertible (Gas)

ETL, US & Canada

Cooking Performance Group G60-NG(CPG) 60" Gas Countertop Griddle with Manual Controls and 60", 2 Drawer Refrigerated Chef Base - 150,000 BTU



Technical Data

Interior Height	16 9/16 Inches
Amps	5 Amps
Phase	1 Phase
Voltage	115 Volts
Wattage	444 Watts
Access Type	Drawers
Base Power Type	Electric
Base Style	Refrigerator
Burner BTU	30000 BTU
Burner Style	U-Shaped
Compressor Location	Side Mounted
Construction	Stainless Steel
Control Type	Manual
Cooking Surface Material	Steel
Horsepower	2/5 hp
Installation Type	Freestanding
Kit Type	Chef Base / Cooking Equipment
Number of Burners	5 Burners
Number of Controls	5 Controls
Number of Drawers	2 Drawers
Plate Thickness	3/4 Inch
Power Type	Natural Gas
Refrigerant Type	R-290
Refrigerator BTU	786 BTU
Starting Amps	15.1 Amps
Starting Wattage	1332 Watts
Temperature Range - Refrigerator	33 - 40 Degrees F
Temperature Settings	Adjustable
Top Style	Marine Edge
Total BTU	150786 BTU
Type	Manual Griddles
Usage	Medium Duty
Weight Capacity	990 lb.

Cooking Performance Group G60-NG(CPG) 60" Gas Countertop Griddle with Manual Controls and 60", 2 Drawer Refrigerated Chef Base - 150,000 BTU



Notes & Details

The Cooking Performance Group 60" countertop griddle boasts 5 powerful 30,000 BTU stainless steel burners with standing pilots for instant ignition that make it a fantastic choice for a variety of cooking tasks, from burgers and bacon to hotcakes and eggs. Manual controls offer added appeal to experienced chefs who prefer the "feel" of manual controls, while the 3/4" thick, 60" wide polished steel cooking surface features an impressive 20" depth that is sure to deliver all of the cooking workspace needed.

The Cooking Performance Group G60-NG(CPG) countertop griddle is made of rugged stainless steel that is both durable and extremely easy to clean, includes back and side splashes to protect your walls and countertops, and even offers a full width waste tray to provide you with the complete package of excellent performance and worry-free maintenance! The unit offers a conveniently located, 3/4" rear gas connection and ships ready to connect to a natural gas supply. The unit includes a liquid propane orifice kit for quick and easy field conversion.

The included Avantco CBE-60-HC 60" 2 drawer refrigerated chef base provides a convenient place for your countertop griddle, with refrigerated space for ingredients. As a space and productivity solution for your kitchen, this chef base makes it easy to increase efficiency by placing the griddle right on top of the chef base where you store your cold ingredients. This base features a durable 1 3/4" stainless steel top that can hold up to 990 lb. of weight. Equipped with a marine edge, the unit's top helps to contain drips and spills for easy cleanup.

Each drawer in this unit can hold up to 3 full size food pans (sold separately). The digital temperature control allows you to set the interior of the unit to hold your prepared foods and ingredients at safe temperatures between 33 and 40 degrees Fahrenheit. The stainless steel construction adds extended durability in a busy kitchen environment. For greater ease of cleaning, casters come included so that you can move the unit away from the wall. The refrigeration system uses a 1/6 hp compressor and R290 refrigerant, which is a safe and environmentally-responsible choice for your business. This refrigerated chef base requires a 115V electrical connection.

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.