#### 35160GTHRBNL

Cooking Performance Group G60T-NG(CPG) 60" Gas Countertop Griddle with Thermostatic Controls and 60", 2 Drawer Refrigerated Chef Base - 150,000 BTU









## Certifications

ـ ("") **ETL Sanitation** 5-15P

3/4" Gas Connection



🚇 ETL, US & Canada

| em #: <u>35160GTHRBNL</u> | Qty:  |  |
|---------------------------|-------|--|
| Project:                  |       |  |
| Approval:                 | Date: |  |

#### Features

- 5 independently-controlled 30,000 BTU burners with continuous pilot for instant ignition
- · Features adjustable thermostatic controls for precision
- Heavy-duty, 3/4" thick steel griddle plate
- Field convertible to liquid propane; includes orifice for connection
- Digital display base uses 1/6 hp; 115V; environmentally friendly R290 refrigerant

#### **Technical Data**

| Width                 | 60 Inches       |
|-----------------------|-----------------|
| Depth                 | 32 1/8 Inches   |
| Height                | 42 9/16 Inches  |
| Cooking Surface Width | 60 Inches       |
| Interior Width        | 48 1/4 Inches   |
| Base Depth            | 32 1/8 Inches   |
| Cooking Surface Depth | 20 Inches       |
| Interior Depth        | 27 9/16 Inches  |
| Top Step Depth        | 60 Inches       |
| Base Height           | 25 13/16 Inches |

#### 35160GTHRBNL

Cooking Performance Group G60T-NG(CPG) 60" Gas Countertop Griddle with Thermostatic Controls and 60", 2 Drawer Refrigerated Chef Base - 150,000 BTU



# Technical Data

| Interior Height                  | 16 9/16 Inches                |
|----------------------------------|-------------------------------|
| Amps                             | 5 Amps                        |
| Phase                            | 1 Phase                       |
| Voltage                          | 115 Volts                     |
| Wattage                          | 444 Watts                     |
| Access Type                      | Drawers                       |
| Base Power Type                  | Electric                      |
| Base Style                       | Refrigerator                  |
| Burner BTU                       | 30000 BTU                     |
| Burner Style                     | U-Shaped                      |
| Compressor Location              | Side Mounted                  |
| Construction                     | Stainless Steel               |
| Control Type                     | Thermostatic                  |
| Cooking Surface Material         | Steel                         |
| Horsepower                       | 1/3 hp                        |
| Installation Type                | Freestanding                  |
| Kit Type                         | Chef Base / Cooking Equipment |
| Number of Burners                | 5 Burners                     |
| Number of Controls               | 5 Controls                    |
| Number of Drawers                | 2 Drawers                     |
| Plate Thickness                  | 3/4 Inch                      |
| Power Type                       | Natural Gas                   |
| Refrigerant Type                 | R-290                         |
| Refrigerator BTU                 | 786 BTU                       |
| Starting Amps                    | 15.1 Amps                     |
| Starting Wattage                 | 1332 Watts                    |
| Temperature Range - Refrigerator | 33 - 40 Degrees F             |
| Temperature Settings             | Adjustable                    |
| Top Style                        | Marine Edge                   |
| Total BTU                        | 150786 BTU                    |
| Туре                             | Thermostatic Griddles         |
| Usage                            | Medium Duty                   |
| Weight Capacity                  | 990 lb.                       |
|                                  |                               |

35160GTHRBNL

Cooking Performance Group G60T-NG(CPG) 60" Gas Countertop Griddle with Thermostatic Controls and 60", 2 Drawer Refrigerated Chef Base - 150,000 BTU



### Notes & Details

The Cooking Performance Group 60" countertop griddle features energy saving thermostats that are adjustable from 200 to 575 degrees Fahrenheit for precise temperature control, making it an excellent choice for delicate breakfast foods like eggs and hotcakes, as well as your lunch menu of chicken, hamburgers, and other meats! The unit boasts 5 powerful 30,000 BTU stainless steel burners with standing pilots for instant ignition that work in perfect harmony with the thermostats to maintain your selected griddle temperature during peak cooking periods. The 3/4" thick, 60" wide polished steel cooking surface features an impressive 20" depth that is sure to deliver all of the cooking workspace needed.

The Cooking Performance Group G60T-NG(CPG) countertop griddle is made of rugged stainless steel that is both durable and extremely easy to clean, includes back and side splashes to protect your walls and countertops, and even offers a full width waste tray to provide you with the complete package of excellent performance and worry-free maintenance! The unit offers a conveniently located 3/4" rear gas connection and ships ready to connect to a natural gas supply. The unit includes a liquid propane orifice kit for quick and easy field conversion.

The included Avantco CBE-60-HC 60" 2 drawer refrigerated chef base provides a convenient place for your countertop griddle, with refrigerated space for ingredients. As a space and productivity solution for your kitchen, this chef base makes it easy to increase efficiency by placing the griddle right on top of the chef base where you store your cold ingredients. This base features a durable 1 3/4" stainless steel top that can hold up to 990 lb. of weight. Equipped with a marine edge, the unit's top helps to contain drips and spills for easy cleanup.

Each drawer in this unit can hold up to 3 full size food pans (sold separately). The digital temperature control allows you to set the interior of the unit to hold your prepared foods and ingredients at safe temperatures between 33 and 40 degrees Fahrenheit. The stainless steel construction adds extended durability in a busy kitchen environment. For greater ease of cleaning, casters come included so that you can move the unit away from the wall. The refrigeration system uses a 1/6 hp compressor and R290 refrigerant, which is a safe and environmentally-responsible choice for your business. This refrigerated chef base requires a 115V electrical connection.

A WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to <u>www.p65warnings.ca.gov</u>.