


FRONT TO BACK DOUBLE HOB

INDUCTION COOKTOP

NON-TOUCH DISPLAY



HELIOS STANDARD, FREESTANDING



HELIOS STANDARD, DROP-IN

TOUCH DISPLAY



HELIOS TOUCH, FREESTANDING

FEATURES

- 2500 and 3500 W models
- Available in 200–240 or 380–415 VAC, single or three phase
- Freestanding or drop-in design with stainless-steel housing
- Front-to-back orientation
- Sloped front panel allows for a freestanding design
- Helios Standard or Helios Touch display options for freestanding design
- High-quality internal electronics and heavy-gauge Litz wire
- Easy-to-clean high-temperature glass-ceramic top
- 4.3-inch display
- Even heat distribution across the bottom of cookware*
- Temperature ranges from 85–425 °F (29–218 °C)
- Automatic pan detection provides instant energy transfer to cookware
- Automatic shut-off feature prohibits overheating
- Integral grease filter and air baffle maintain cooler, cleaner air intake
- Integral fan to keep internal components cool
- Microprocessors continuously monitor vital components for overheating, power-supply issues, and other conditions

STANDARD INCLUDED ACCESSORIES


- Two-year advanced replacement warranty (U.S. and Canada)
- Standard Cat 5e or Cat 6 patch cable from unit to control box
- 6-ft (1.8 m) nominal plug and cord




*Induction cooking requires the use of induction-compatible (i.e., magnetic) cookware.

It is the owner and installer's responsibility to comply with all local codes. CookTek reserves the right to substitute components or change specifications without prior notice.


HELIOS
STANDARD
FREESTANDING



HELIOS
STANDARD
DROP-IN



HELIOS TOUCH
FREESTANDING



DIMENSIONS - HELIOS STANDARD FREESTANDING		
Full Unit Height	5"	127 mm
Full Unit Width	13.7"	347 mm
Full Unit Depth	32.3"	819 mm
Feet Height	1.2"	31 mm
Weight	31 lb	14 kg
Max Ambient Temperature	122 °F	50 °C

DIMENSIONS - HELIOS STANDARD DROP-IN		
Full Unit Height	3.7"	95 mm
Full Unit Width	13.5"	343 mm
Housing Width	12.8"	324 mm
Full Unit Depth	27.3"	692 mm
Housing Depth	26.5"	673 mm
Cutout Width	13.13"	334 mm
Cutout Depth	26.88"	683 mm
Weight	30 lb	13.6 kg
Max Ambient Temperature	122 °F	50 °C

DIMENSIONS - HELIOS TOUCH FREESTANDING		
Full Unit Height	5"	127 mm
Full Unit Width	13.7"	347 mm
Full Unit Depth	32.3"	819 mm
Feet Height	1.2"	31 mm
Weight	31 lb	14 kg
Max Ambient Temperature	122 °F	50 °C

WALL CLEARANCE*		
Front	2"	51 mm
Sides	2"	51 mm
Rear	2"	51 mm

*The clearances provided apply to a unit not placed near a heat source. Refer to the owner's manual for clearance requirements if the unit is placed near a heat source.



56PA332, 32 A, 250 V



IEC 309, 5-pin, 16 A



NEMA 6-30P



IEC 309, 3-Pin, 32 A, 240 V



IEC 309, 5-pin, 32 A



NEMA 6-50P

SHIPPING INFORMATION		
Packaged Height	11"	279 mm
Packaged Width	23"	584 mm
Packaged Depth	32"	813 mm
Packaged Weight	40 lb	18.14 kg
Item Class	250 NMFC #26710	

ELECTRICAL SPECIFICATIONS - SINGLE PHASE HELIOS STANDARD FREESTANDING		
UNITED STATES/CANADA		
HRF-9500-FB25-1	200-240 VAC, 50/60 Hz, 2x2500 W	NEMA 6-30P
HRF-9500-FB35-1	200-240 VAC, 50/60 Hz, 2x3500 W	NEMA 6-50P
UK/MIDDLE EAST		
HRF-9500-FB25-2	200-240 VAC, 50/60 Hz, 2x2500 W	IEC 309, 3-Pin, 32 A, 240 V
HRF-9500-FB35-2	200-240 VAC, 50/60 Hz, 2x3500 W	IEC 309, 3-Pin, 32 A, 240 V
INTERNATIONAL		
HRF-9500-FB25-3	200-240 VAC, 50/60 Hz, 2x2500 W	IEC 309, 3-Pin, 32 A, 240 V
HRF-9500-FB35-3	200-240 VAC, 50/60 Hz, 2x3500 W	IEC 309, 3-Pin, 32 A, 240 V
AUSTRALIA		
HRF-9500-FB25-4	200-240 VAC, 50/60 Hz, 2x2500 W	56PA332, 32 A, 250 V
HRF-9500-FB35-4	200-240 VAC, 50/60 Hz, 2x3500 W	56PA332, 32 A, 250 V
JAPAN		
HRF-9500-FB25-6	200-240 VAC, 50/60 Hz, 2x2500 W	NEMA 6-30P
HRF-9500-FB35-6	200-240 VAC, 50/60 Hz, 2x3500 W	NEMA 6-50P
SOUTH AFRICA		
HRF-9500-FB25-7	200-240 VAC, 50/60 Hz, 2x2500 W	IEC 309, 3-Pin, 32 A, 240 V
HRF-9500-FB35-7	200-240 VAC, 50/60 Hz, 2x3500 W	IEC 309, 3-Pin, 32 A, 240 V
ISRAEL		
HRF-9500-FB25-8	200-240 VAC, 50/60 Hz, 2x2500 W	IEC 309, 3-Pin, 32 A, 240 V
HRF-9500-FB35-8	200-240 VAC, 50/60 Hz, 2x3500 W	IEC 309, 3-Pin, 32 A, 240 V

ELECTRICAL SPECIFICATIONS - SINGLE PHASE HELIOS STANDARD DROP-IN		
UNITED STATES/CANADA		
HRD-9500-FB25-1	200-240 VAC, 50/60 Hz, 2x2500 W	NEMA 6-30P
HRD-9500-FB35-1	200-240 VAC, 50/60 Hz, 2x3500 W	NEMA 6-50P
UK & SAUDI ARABIA		
HRD-9500-FB25-2	200-240 VAC, 50/60 Hz, 2x2500 W	IEC 309, 3-Pin, 32 A, 240 V
HRD-9500-FB35-2	200-240 VAC, 50/60 Hz, 2x3500 W	IEC 309, 3-Pin, 32 A, 240 V

ELECTRICAL SPECIFICATIONS - SINGLE PHASE HELIOS STANDARD DROP-IN		
INTERNATIONAL		
HRD-9500-FB25-3	200–240 VAC, 50/60 Hz, 2x2500 W	IEC 309, 3-Pin, 32 A, 240 V
HRD-9500-FB35-3	200–240 VAC, 50/60 Hz, 2x3500 W	IEC 309, 3-Pin, 32 A, 240 V
AUSTRALIA		
HRD-9500-FB25-4	200–240 VAC, 50/60 Hz, 2x2500 W	56PA332, 32 A, 250 V
HRD-9500-FB35-4	200–240 VAC, 50/60 Hz, 2x3500 W	56PA332, 32 A, 250 V
JAPAN		
HRD-9500-FB25-6	200–240 VAC, 50/60 Hz, 2x2500 W	NEMA 6-30P
HRD-9500-FB35-6	200–240 VAC, 50/60 Hz, 2x3500 W	NEMA 6-50P
SOUTH AFRICA		
HRD-9500-FB25-7	200–240 VAC, 50/60 Hz, 2x2500 W	IEC 309, 3-Pin, 32 A, 240 V
HRD-9500-FB35-7	200–240 VAC, 50/60 Hz, 2x3500 W	IEC 309, 3-Pin, 32 A, 240 V
ISRAEL		
HRD-9500-FB25-8	200–240 VAC, 50/60 Hz, 2x2500 W	IEC 309, 3-Pin, 32 A, 240 V
HRD-9500-FB35-8	200–240 VAC, 50/60 Hz, 2x3500 W	IEC 309, 3-Pin, 32 A, 240 V

ELECTRICAL SPECIFICATIONS - SINGLE PHASE HELIOS TOUCH FREESTANDING		
UNITED STATES/CANADA		
HTF-9500-FB25-1	200–240 VAC, 50/60 Hz, 2x2500W	NEMA 6-30P
HTF-9500-FB35-1	200–240 VAC, 50/60 Hz, 2x3500W	NEMA 6-50P
UK & SAUDI ARABIA		
HTF-9500-FB25-2	200–240 VAC, 50/60 Hz, 2x2500 W	IEC 309, 3-Pin, 32 A, 240 V
HTF-9500-FB35-2	200–240 VAC, 50/60 Hz, 2x3500 W	IEC 309, 3-Pin, 32 A, 240 V
INTERNATIONAL		
HTF-9500-FB25-3	200–240 VAC, 50/60 Hz, 2x2500 W	IEC 309, 3-Pin, 32 A, 240 V
HTF-9500-FB35-3	200–240 VAC, 50/60 Hz, 2x3500 W	IEC 309, 3-Pin, 32 A, 240 V
AUSTRALIA		
HTF-9500-FB25-4	200–240 VAC, 50/60 Hz, 2x2500 W	56PA332, 32 A, 250 V
HTF-9500-FB35-4	200–240 VAC, 50/60 Hz, 2x3500 W	56PA332, 32 A, 250 V
JAPAN		
HTF-9500-FB25-6	200–240 VAC, 50/60 Hz, 2x2500 W	NEMA 6-30P
HTF-9500-FB35-6	200–240 VAC, 50/60 Hz, 2x3500 W	NEMA 6-50P
SOUTH AFRICA		
HTF-9500-FB25-7	200–240 VAC, 50/60 Hz, 2x2500 W	IEC 309, 3-Pin, 32 A, 240 V
HTF-9500-FB35-7	200–240 VAC, 50/60 Hz, 2x3500 W	IEC 309, 3-Pin, 32 A, 240 V
ISRAEL		
HTF-9500-FB25-8	200–240 VAC, 50/60 Hz, 2x2500 W	IEC 309, 3-Pin, 32 A, 240 V

ELECTRICAL SPECIFICATIONS - SINGLE PHASE HELIOS TOUCH FREESTANDING		
HTF-9500-FB35-8	200–240 VAC, 50/60 Hz, 2x3500 W	IEC 309, 3-Pin, 32 A, 240 V

ELECTRICAL SPECIFICATIONS THREE PHASE HELIOS STANDARD FREESTANDING		
UK & SAUDI ARABIA		
HRF-9500-FB25-11	380–415 VAC, 50/60 Hz, 2X2500 W	IEC 309, 5-pin, 16 A
HRF-9500-FB35-11	380–415 VAC, 50/60 Hz, 2X3500 W	IEC 309, 5-pin, 32 A
INTERNATIONAL		
HRF-9500-FB25-12	380–415 VAC, 50/60 Hz, 2X2500 W	IEC 309, 5-pin, 16 A
HRF-9500-FB35-12	380–415 VAC, 50/60 Hz, 2X3500 W	IEC 309, 5-pin, 32 A

ELECTRICAL SPECIFICATIONS THREE PHASE HELIOS STANDARD DROP-IN		
UK & SAUDI ARABIA		
HRD-9500-FB25-11	380–415 VAC, 50/60 Hz, 2X2500 W	IEC 309, 5-pin, 16 A
HRD-9500-FB35-11	380–415 VAC, 50/60 Hz, 2X3500 W	IEC 309, 5-pin, 32 A
INTERNATIONAL		
HRD-9500-FB25-12	380–415 VAC, 50/60 Hz, 2X2500 W	IEC 309, 5-pin, 16 A
HRD-9500-FB35-12	380–415 VAC, 50/60 Hz, 2X3500 W	IEC 309, 5-pin, 32 A

ELECTRICAL SPECIFICATIONS THREE PHASE HELIOS TOUCH FREESTANDING		
UK & SAUDI ARABIA		
HTF-9500-FB25-11	380–415 VAC, 50/60 Hz, 2X2500 W	IEC 309, 5-pin, 16 A
HTF-9500-FB35-11	380–415 VAC, 50/60 Hz, 2X3500 W	IEC 309, 5-pin, 32 A
INTERNATIONAL		
HTF-9500-FB25-12	380–415 VAC, 50/60 Hz, 2X2500 W	IEC 309, 5-pin, 16 A
HTF-9500-FB35-12	380–415 VAC, 50/60 Hz, 2X3500 W	IEC 309, 5-pin, 32 A

⚠️ Dedicated circuit required for each installation