# AquaTuff™ Wrap&Stow™ Waterproof Thermocouple Instruments

351 / 352

The AquaTuff™ Wrap&Stow™ instruments are the best choice when accuracy is your top priority. There are 3 models to choose from: DuraNeedle, MicroNeedle or Bell Surface Probe. The DuraNeedle and MicroNeedle probes are calibrated with the instrument for Total System Accuracy™. The heavy-duty patented probe cable is reinforced and neatly wraps and stows around the instrument. All AquaTuff™ instruments are IPX7 waterproof rated and durable for use in harsh environments.









# **Specifications**

- Temperature Range: -100° to 500°F (-73° to 260°C)
- Resolution: 0.1°
- · Waterproof: IPX7 rated
- · Uses any Type K probe
- Large, easy-to-read LCD screen
- °F / °C selectable
- · Auto Shut-off: After 10 minutes of non-use
- · Modes: Hold, backlight (Only offered on the 352 Series)
- · Housing: ABS Plastic
- Power Source: Two (2) 1.5V AAA battery 1800 hours battery life
- Traceability: Instrument calibration constants stored in non-volatile memory to temperature and / or electrical standards traceable to the U.S. Department of Commerce National Institute of Standards and Technology (NIST). Under normal operating conditions, it will not need to be recalibrated.
- 5-year instrument warranty, 1-year probe warranty
- · CE, WEEE and RoHS compliant



#### 35132 / 35232 / 35140 / 35240

- Accuracy: ±0.9°F (±0.5°C) (total system accuracy)
- NSF listed



#### 35135 / 35235

• Accuracy: 0.5°F (±0.3C) (instrument only)

Surface probe temperature errors for draft-free, clean oiled surfaces with 2.2 lbs of pressure are typically within +2.7°F and -6.3°F without thermostat recycling.

### **Packaging**

## 35132 / 35232 / 35140 / 35240

- Individual Package Weight: 10 oz (283 g)
- Package Dimensions: 9" x 4.375" x 2.125" (229 mm x 111 mm x 54 mm)
- · Package Cube: 0.05

## 35135 / 35235

- Individual Package Weight: 12 oz (340 g)
- Package Dimensions: 9.75" x 4.25" x 3.25"
  (248 mm x 108 mm x 83 mm)
- Package Cube: 0.08





