


# 5014R PVC

## CUSTOMER SPECIFICATION

<b>Product Nomenclature</b>	<b>Manufacturing Glove Code:</b> 5014R <b>Manufacturing Glove Name:</b> Generic
<b>Product Description</b>  	<b>Product Class:</b> Supported PVC Gloves <b>Liner Composition:</b> 100% Cotton Interlock <b>Coating Composition:</b> Black Polyvinyl Chloride <b>Sizes:</b> Large <b>Packaging:</b> 12 pairs/inner polybag, 72 pairs/case <b>Exterior Finish:</b> Rough Finish <b>Cuff Type:</b> 14-inch Gauntlet <b>Overedge:</b> Not Applicable <b>Overall Length:</b> 35 cm. <b>Glove Markings:</b> None <b>Size:</b> Men's Large <b>Case Pack:</b> Six Dozen
<b>Characteristics &amp; Applications</b>	<ul style="list-style-type: none"> <li>• Durable PVC for Abrasion Resistance</li> <li>• Chemical Splash Protection</li> <li>• Excellent Protection against Oils, greases, detergents a</li> <li>• 100% Cotton Interlock Fabric for all-day comfort and perspiration absorption</li> <li>• Applications: Petrochemical Industry, Refining Operations, Materials Handling, Handling Valves &amp; Pipes, Degreasing Operations and Equipment Cleaning</li> <li>• Generally PVC provides protection against acids, oils, fats, petroleum hydrocarbons, glycol ethers, alcohols and caustics.</li> </ul>
<b>Typical Performance Values</b>	<b>Thickness:</b> 0.55 mm (+/- .165 mm) <b>Abrasion Resistance:</b> EN388 Level 4 <b>Cut Resistance:</b> EN388 Level 1 <b>Tear Resistance:</b> EN388 Level 2 <b>Puncture Resistance:</b> EN388 Level 1
<b>Quality System</b>	Not Applicable
<b>Shelf Life</b>	Five Years
<b>Country of Origin</b>	China
<b>Originator</b>	Scott M. Laxton/Marketing Director
<b>Date</b>	August 9, 2010



**Corporate Headquarters:** 2085 W.E. Freeman Drive, Memphis, TN 38114  
 Phone 901.458.5030 Fax 901.458.3343  
**West Coast Office:** 13850 Central Avenue, Suite 300, Chino, CA 91710  
 Phone 909.590.2679 Fax 909.590.3130  
**Website:** [www.cordovaisc.com](http://www.cordovaisc.com)