



DT301XC/ DT301X Rugged Tablets

Slim, Rugged, Multi-functional Wireless Computing

The DT301 Series Rugged Tablet features the integration of a high brightness 10.1" capacitive touch screen and a high performance, energy-efficient Intel® processor within a slim, lightweight, durable package. With built-in Wi-Fi and Bluetooth as well as options for barcode scanner, 3D camera, GNSS, and 4G connection, this robust tablet offers seamless information capture and transmission for improved workflow. Rated IP65, MIL-STD-810G and MIL-STD-461F, the DT301 Series Rugged Tablet provides reliable operation in harsh, mission-critical environments.



Features

- 10.1" high-brightness capacitive touch screen (800 nits), digital pen support
- Intel® Celeron® or 8th Generation Core™ i5/i7 processor
- Microsoft® Windows® 10 IoT Enterprise operating system
- NIST compliant BIOS available
- High capacity, hot-swappable battery pack
- IP65 rated, MIL-STD-810G and MIL-STD-461F certified
- Build-in smart card/ CAC reader (DT301T)

Major Options

- Front and back cameras
- Intel® RealSense™ Depth camera (DT301X)
- Barcode scanner
- U-blox M8 GNSS module
- 4G LTE/AWS

Specifications



Model	DT301XC	DT301X
System		
CPU	Intel® Celeron® 3955U , Dual-Core, 2.0GHz	Intel® Core™ i5-8250U, Quad-Core, 1.6GHz (up to 3.4GHz) Intel® Core™ i7-8550U, Quad-Core, 1.8GHz (up to 4.0GHz)
RAM	8GB	8GB to 16GB
Storage	256GB Flash	256GB to 2TB Flash
Operating System	Microsoft® Windows® 10 IoT Enterprise	
NIST Compliance	NIST compliant BIOS available	NIST compliant BIOS available
Display	10.1” high-brightness (800 nits) screen with capacitive touch, outdoor viewable	
Display Resolution	1920 x 1200	1920 x 1200
Fan/ Fanless	Fanless	Fanless
Control Switch and Buttons	1 power button, 3 programmable buttons, 1 RF switch	
Microphone	Built-in microphone	Built-in microphone
Speaker	Built-in speaker	Built-in speaker
Network Interface		
WLAN	Wi-Fi 802.11ac, 2.4GHz/ 5GHz dual band	Wi-Fi 802.11ac, 2.4GHz/ 5GHz dual band
Bluetooth	Bluetooth 4.2 LE	Bluetooth 4.2 LE
I/O Ports		
USB Ports	USB 3.0 x 1 and USB Type-C x 1	USB 3.0 x 1 and USB Type-C x 1
Headset Jack	1 (3.5mm)	1 (3.5mm)
DC-in	1	1
Ethernet	Ethernet 10/ 100/ 1000MB Base-T LAN	Ethernet 10/ 100/ 1000MB Base-T LAN
Mechanical and Environmental		
AC/DC Adapter	Input: 100-240V AC; Output: 19V DC, 3.42A	Input: 100-240V AC; Output: 19V DC, 3.42A
Battery Pack	Hot Swappable battery, 7.2V, 6150mAh	Hot swappable battery, 11.4V, 5400mAh; Hot swappable battery, 11.4V, 8000mAh (optional)
Enclosure		
Dimensions (H x W x D)	7.8 x 11 x 0.86 in/ 198 x 280 x 21.9 mm	7.8 x 11 x 0.86 in/ 198 x 280 x 21.9 mm
Weight	3.1 lbs/ 1.4 kg	3.1 lbs/ 1.4 kg
Durability	IP65, MIL-STD-810G and MIL-STD-461F certified	
Regulatory	FCC Class B, CE, RoHS compliant	
Temperature	Operation: -20°C – 45°C (-4°F – 113°F, AC mode), 0°C – 45°C (32°F – 113°F, battery mode); Storage: -55°C – 70°C (-67°F to 158°F)	Operation*: -20°C to 60°C (-4°F to 140°F), tested under MIL-STD-810G method 501.6, Procedure II, and method 502.6, Procedure II Storage: -55°C to 70°C (-67°F to 158°F)
Humidity	0% – 90% non-condensing	
Major Options		
Barcode Scanner	2D scanner, reads 1D also	
Camera	8 megapixel back camera with auto focus, white balance, gain control, and exposure control	8 megapixel back camera; or, Intel® RealSense™ Depth back camera, supports distance capture for the 3D scanning, environment sensing and background segmentation applications
Camera Light	External camera LED light with mounting bracket	
Long Range Bluetooth	Class 1 Bluetooth (1000 ft)	Class 1 Bluetooth (1000 ft)
GNSS Module	U-blox M8 GNSS module with concurrent reception of GPS and GLONASS; industry leading -167dBm navigation sensitivity	
Mobile Broadband	4G LTE/AWS	4G LTE/AWS

* Specifications subject to change without notice.

** For battery safety, optimal functionality and performance, the recommended usage temperature range is from -10°C to 45°C (14°F to 113°F).

