ES300™ ST/XP & ES400™ XLP

Self Contained Carpet Extractors



Cleaning Carpet Spaces in a Big Way.

With the introduction of the ES300™ and ES400™ self contained extractors, Advance has entered a new era of carpet cleaning. Built on the industry leading AquaClean® platform, these multi-purpose machines are ideal for cleaning your high-traffic carpeted areas. Featuring LIFT™ as well as our Dual Cleaning Mode technologies, the ES300™ XP and ES400™ XLP allow you to perform deep cleaning or interim cleaning with super-quick dry times. With the Carpet and Rug Institute Seal of Approval, you can be certain that these machines not only thoroughly remove dirt and water, but also meet the highest standards in the industry to help extend the life of your carpets.

A better design for greater productivity.

With multiple new features that decrease time-to-clean, the ES300™ XP and ES400™ XLP models were designed to improve staff productivity. For example, each cleaning mode (*LIFT*™ Mode, Deep Clean and Pre-Treat) can be quickly engaged directly from the panel. Plus, these machines are designed with increased tank capacity for extended operation as well as improved water pickup capability for faster drying.

Making tough jobs easier.

The ES300 and ES400 not only increase productivity, they're also very easy to operate. One convenient feature is the front-mounted drain hose, which makes emptying the tank much simpler. Integrated hand tool (standard on XP and XLP models) prevents the loss and expense of replacement parts, and the brush head creates greater contact with the carpet and improved suction, leaving carpets dryer after cleaning. Finally, the compact design makes storage and maintenance much more convenient. These innovative features, among others, are why Advance machines are some of the most cutting edge and user-friendly available, making cleaning easier.

LIFT™ your facility to a new level of clean.

The ES300 XP and ES400 XLP both feature the proprietary *LIFT*™ technology, allowing for incredibly fast dry times. This patented Low-moisture — Interim-cleaning — Fast-dry time — True-cleaning system consists of a single spray nozzle that eliminates streaking and overlaps that lead to longer drying times. *LIFT* gives your carpets a thorough clean yet leaves them ready for traffic in as little as 30 minutes, making these machines ideal for high-traffic areas and daytime cleaning.

Accessories and Options

- 16 inch (41 cm) nylon standard carpet brush (pn 56265044)
- 16 inch (41 cm) nylon hard floor brush (pn 56265175)
- 16 inch (41 cm) MidGrit 240 hard floor brush (pn 56265176)
- 18 inch (46 cm) nylon standard carpet brush (pn 56265099)
- 18 inch (46 cm) nylon hard floor brush (pn 56265177)
- 18 inch (46 cm) MidGrit 240 hard floor brush (pn 56265178)
- Wand assembly with soft and hard floor tools (pn 56314402)
- Wand assembly with soft floor tool (pn 56265173)
- Hand upholstery tool (pn 56220070)
- Heavy duty soft floor wand (pn 56265305)
- Plug adaptor kit (pn 56265309)
- 15 foot (4.6 m) solution and recovery hose assembly (pn 56265174)
- Hose assembly 96 inches (pn 56265753)
- Hose assembly 184 inches (pn 56265754)
- Hand tool / hoses assembly (pn 56265767)
- Hand tool / hoses assembly upgrade for ES300 ST (pn 56265810)
- Hard floor tool assembly (pn 56265675)

Typical Applications Include

- Schools
- Healthcare Facilities
- Small Businesses
- Offices
- Retailers





ES300™ ST/XP & ES400™ XLP

Self Contained Carpet Extractors



All cleaning modes are mounted on the panel for quick engagement and easy operation. (XP and XLP models)



An adjustable handle allows for easy maneuverability, decreasing the need for backing into tight spaces. (ES400™ XLP shown)



The front-mounted nozzle makes dumping much faster and easier for the operator.



Simply flip a switch to easily shift from spotting to extraction mode.



The removable, increased capacity tank along with the stowable handle make refilling much simpler.

- The front-mounted drain hose allows for faster and easier dumping for the operator
- Integrated hand tool offers quick access and eliminates the need for replacement parts (standard on XP and XLP models)
- A floating brush head needs no adjusting, creating better carpet 3 contact and improved water recovery
- The removable tank with stowable handle makes the re-filling process far less cumbersome
- All cleaning modes are mounted on the panel for quick engagement and easy operation
- A larger tank with increased water capacity provides extended cleaning time and
- New handle design means improved maneuverability in tight spaces





Defining Cleaning Innovation...

- Our products are designed using innovative technology that increases productivity and drives down the cost to clean.
- You can get expert service and maintenance for your Advance machines from factorytrained personnel around the world. Fast parts delivery, too.
- Maintain peak performance with Nilfisk Parts.

Technical Specifications

Models	ES300™ ST	ES300™ XP	ES400™ XLP
Cleaning Path	16 in (41 cm)	16 in (41 cm)	18 in (46 cm)
Solution Tank	9 gal (34 L)	9 gal (34 L)	12 gal (45 L)
Recovery Tank	7 gal (26.5 L)	7 gal (26.5 L)	10 gal (38 L)
Pump	120 psi	120 psi	120 psi
Flow Rate Interim Cleaning Mode	N/A	0.17 gpm	0.17 gpm
Flow Rate Restorative Mode	0.7 gpm	0.7 gpm	0.7 gpm
Vacuum Motor	1.5 hp 2 stage	1.5 hp 2 stage	1.5 hp 2 stage
Waterlift	120 in	120 in	120 in
Brush Motor	1/3 hp	1/3 hp	1/3 hp
Brush Size	16 in (41 cm)	16 in (41 cm)	18 in (46 cm)
Vacuum Shoe Size	18.75 in (48 cm)	18.75 in (48 cm)	20.75 in (53 cm)
Flip Handle	No	No	Yes
Power Cable	50 ft	50 ft	50 ft
Minimum Machine Length	28 in	28 in	29.25 in
Machine Width	19.25 in	19.25 in	22.75 in
Tank Height	32 in	32 in	35.25 in
Gross Weight	102 lb	106 lb	118 lb
Sound	68 dB A	68 dB A	68 dB A
Model Numbers	56265502	56265500	56265501

Specifications are subject to change without notice.





Nilfisk, Inc.

9435 Winnetka Avenue North Brooklyn Park, MN 55445 www.advance-us.com Phone 800-850-5559 Fax 800-989-6566

240 Superior Boulevard Mississauga, Ontario, Canada L5T 2L2 www.nilfisk-advance.ca Phone 800-668-8400 Fax 800-263-5111



