



Estella
Caffe

Item #: 236ECTPM2 Project: _____

Qty: _____ Date: _____ Approval: _____

Estella Caffe ECTPM2 Two Group Teapresso Machine

Item #236ECTPM2




Technical Data

Width	28 5/8 Inches
Depth	21 3/4 Inches
Height	22 5/8 Inches
Amps	23 Amps
Hertz	50/60 Hz
Voltage	220 - 240 Volts
Wattage	4500 Watts
Application	Tea Brewers
Boiler Capacity	3 gal.
Color	Silver

Features

- Four easy programmable settings per group head
- Includes a hot water outlet and steam wands
- Automatic cleaning for easy maintenance
- Multi-boiler preheating and heat system for water flow endurance and temperature stability
- Perfect for serving traditional, herbal, and fruit teas

Certifications



Technical Data

Features	Hot Water Faucet NSF Listed
Number of Groups	2 Groups
Number of Steam Wands	1 Wands
Plug Type	Hardwire
Style	Automatic
Type	Tea Brewers
Water Inlet Size	3/8 Inches
Water Source	Direct Connection

Notes & Details

Make and serve a wide variety of teas with this Estella Caffe two group teapresso machine. This machine is perfect for serving traditional, herbal, and fruit teas and provides unlimited combinations of drink options. It features 2 tea portafilters and 2 group heads, and it's easily programmable with four settings for each group head. Programmable settings allow customers to set the amount of tea dispensed and the temperature, ensuring each cup of tea is consistent. It comes with a steam wand, a hot water outlet, and (2) 1.5 gallon broilers.

This unit eliminates the need for extra equipment such as tea barrels and hot water dispensers, taking up less room in your busy kitchen. Additionally, it features a 90-second extraction to get the best flavor and aroma from your tea drinks. To ensure every drink is fresh and ready to consume, this machine allows the tea to be brewed per order by the cup.

This teapresso machine combines a minimal design with its metallic texture and diamond black side panels. Plus, its independent auto-cleaning function makes cleaning and maintaining this unit easy. Thanks to its multi-boiler preheating and heat system, this machine ensures water flow endurance and temperature stability. This unit has a 29-43 PSI and a 3/8" male NPT fitting, and it requires a 220/240V electrical connection for operation.

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.