

ltem#:	348DSF78		Project:		
Qty:		Date:		Approval:	

Estella DSF78 85" Floor Reversible Dough Sheeter - 110V, 3/4 hp

Item #348DSF78







Technical Data

Width	88 9/16 Inches		
Depth	34 5/8 Inches		
Height	46 7/16 Inches		
Conveyor Length	85 Inches		
Conveyor Width	19 3/4 Inches		
Folded Width	29 1/2 Inches		
Folded Depth	39 5/8 Inches		
Folded Height	63 Inches		
Amps	4.67 Amps		
Hertz	60 Hz		

Features

- Easily adjustable for any dough thickness between 1/32" and 1 3/8"
- Spacious 19 3/4" x 85" conveyor belt; 20 1/2" roller allows 11 lb. of dough at a
- Reversible belt and durable stainless steel body for versatile, high-volume use
- Includes casters for mobility and folds up for compact storage
- Perfect for bakeries or pizzerias; 110V, 560W

Certifications








ETL Sanitation ETL, US & Canada



Technical Data

Phase	1 Phase		
Voltage	110 Volts		
Wattage	560 Watts		
Belt Material	Polyurethane		
Dough Capacity	11 lbs.		
Horsepower	3/4 hp		
Maximum Dough Thickness	1 3/8 Inches		
Minimum Dough Thickness	1/32 Inch		
Plug Type	NEMA 5-15P		
Power Type	Electric		
Style	Floor Model		
Transmission Type	Belt-Driven		
Туре	Reversible Dough Sheeters		

Plan View



Notes & Details

Save time and labor in your bakery or pizzeria by adding this Estella 85" reversible floor model dough sheeter to your preparation area. Designed to quickly roll out several pounds of dough per minute, this sheeter features a 20 1/2" roller and can produce dough thickness between 1/32" and $1\,3/8$ ". The roller is equipped to roll up to 11 lb. of dough at a time, perfect for high-volume operations. It utilizes a $19\,3/4$ " wide conveyor to move dough through the machine, and the conveyor is reversible for quick rolling from either side of the unit to accommodate the flow of your operation.

This model is made of durable, corrosion-resistant stainless steel to withstand the rigors of commercial environments while remaining easy to clean at the end of the day. The supports on either end of the machine fold up for space-saving storage, and the entire unit is supported on four 2 1/2" casters, two of which lock to keep the unit in place when necessary. It also has several safety features to prevent worker injuries or damage to the motor, including safety guards and an emergency stop switch. A 110V electrical connection is required for operation.

MARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.