

THREE STATION FLOOR MOUNTED SINK WITH TUBULAR LEGS

TOE-PUSH OPERATED







ltem #:	Qty #:
Model #:	
Project #:	



FEATURES:

8 1/2" high backsplash.

8" sink bowl depth.

Stainless steel "Z" brackets (2) supplied each unit.

One K-6 3 1/2" rear basket drain.

Four tubular stainless steel legs with stainless steel bullet feet.

One stainless steel support shelf with rear turn-up.

Toe-Push Operated: Includes three K-104 toe-push valves and three K-121 spouts.

Single holes provided.

CONSTRUCTION:

All TIG welded.

Welded areas blended to match adjacent surfaces and to a satin finish.

Die formed tubular wall brackets.

MATERIAL:

All 16 gauge type "304" stainless steel. 1 5/8" tubular "304" stainless steel legs. Stainless steel gussets.

MECHANICAL:

Single faucet holes.

		# of	# of		Cu.
Model #	Length	Spouts	Legs	Wt.	Ft.
FC-WM-60FV	60"	3	4	118 Lbs.	43



MULTI-STATION ACCESSORIES & REPLACEMENT PARTS Model Description QTY: **₩** K-6 3 1/2" Drain (1 1/2" I.P.S.) K-121 **K-06** Splash Mount Faucet Mounting Kit K-104 Stainless Steel Soap Dispenser (Wall Mount Only) **K-13** Toe-Push Valve Assembly **K-104** K-411 **K-121** Single Hole, Splash Mounted 3-1/2" Gooseneck Spout **K-411** Strainer Plate for 3-1/2" Drain Special Sizing Charge (Larger Size **K-508** TA-19 Cut Down To Smaller Size) **TA-19** Adjustable Stainless Steel Flanged Bullet Foot

= Ships UPS

Standard Faucets conform to NSF 61 Standard 9 and compliance to AB 1953 Standards.

MARNING: Equipment that include faucets on this page may contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes: Email: smartfab@advancetabco.com or Fax: 631-586-2933 TOL ± .500" ALL DIMENSIONS ARE TYPICAL



