

FOUR STATION WALL MOUNTED SINK WITH TUBULAR SUPPORTS

ELECTRONIC OPERATED



| Item #:_____ Qty #: _____ | Model #: _____ | Project #: _____





FEATURES:

8 1/2" high backsplash.

8" sink bowl depth.

Two stainless steel "Z" brackets supplied each unit.

One K-6 3 1/2" rear basket drain.

Two tubular stainless steel support brackets that allow full clearance underneath.

Electronic Operated: Includes four **K-175** Electronic Faucets. Single holes provided.

CONSTRUCTION:

All TIG welded.

Welded areas blended to match adjacent surfaces and to a satin finish.

Die formed tubular wall brackets.

MATERIAL:

All 16 gauge type "304" stainless steel.

1 5/8" tubular "304" stainless steel wall brackets.

Stainless steel gussets.

MECHANICAL:

Single faucet holes.

		# 01	# OT		Cu.
Model #	Length	Faucets	Wall Supports	Wt.	Ft.
FC-WM-80EF	80"	4	2	100 Lbs.	28

Click Here For Install Guide

MULTI-STATION ACCESSORIES & REPLACEMENT PARTS



FLOOR STANDING LEGS MODIFICATION

Converts Wall Mounted FS-WM SERIES Sink To A Free Standing Floor Unit.

- Stainless Steel Legs with Flanged Feet
- Sides and Rear Cross Bracing

	Fits Sink	
Model #	Length	QTY:
FS-CB-80	80"	



= Ships UPS

Standard Faucets conform to NSF 61 Standard 9 and compliance to AB 1953 Standards.

WARNING: Equipment that include faucets on this page may contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes: Email: smartfab@advancetabco.com or Fax: 631-586-2933 TOL ± .500" ALL DIMENSIONS ARE TYPICAL



