☐ 62669 W/ 6" SWIVEL/RIGID GOOSENECK SPOUT

W/ LEVER HANDLES

☐ 62502 W/ 12" SWIVEL/RIGID GOOSENECK SPOUT

W/ LEVER HANDLES

☐ 62677 W/ 6" SWIVEL/RIGID GOOSENECK SPOUT

W/ WRIST HANDLES

☐ 62510 W/ 12" SWIVEL/RIGID GOOSENECK SPOUT

W/ WRIST HANDLES

## **FEATURES**

#### **CONTROL VALVE**

- \* 4" C/C BACKSPLASH
- \* CONCENTRICS
- \* STAINLESS STEEL CONSTRUCTION
- \* SWIVELLING SEAT DISKS
- \* HOT SIDE STEM RIGHT HAND
- \* COLD SIDE STEM LEFT HAND
- \* LEVER HANDLES OR WRIST HANDLES
- \* GOOSENECK SPOUT


#### SYSTEM LIMITS

- \* TEMP: 40°F MIN. TO 140°F MAX.
- \* PRESSURE: 200 PSI MAX. STATIC
- \* 2.20 GPM AT 80 PSI

## SHIPPING WEIGHT


\* 5.0 LBS

\* NSF 61-9 APPROVED & LISTED www.truesdail.com




4" BACKSPLASH FAUCET W/ LEVER HANDLES

# 4" BACKSPLASH FAUCET W/ WRIST HANDLES




# 4" C/C BACKSPLASH FAUCET



### ROUGH-IN:

# BACKSPLASH



ANSI/A112.18.1-2005

DIM "C" **MODELS** DIM "A" DIM "B" 62669 4-1/2" 8-1/16" 3-1/2" 62677 [114.3mm] [204.8mm] [88.90mm] 62502 8-1/4" 12-1/4" 5-1/2" 62510 [209.6mm] [311.2mm] [139.7mm]

FISHER MANUFACTURING COMPANY

TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com