

FIXED STEEL LADDERS



A Division of Ballymore Safety Products

FEATURES

- Side rail 2 - 1/2" x 3/8" flat bar
- Solid round 3/4" rungs
- 12" spacing between rungs
- 18" ladder width
- 42" guardrails on walk-thru models
- Powder-coat yellow finish
- Ships in components for freight savings
- Complies with applicable OSHA & ANSI standards



**Uncaged ships
in a box for huge
freight savings!**



**Without Cage/
Walk Thru**



**Cage/Walk
Thru All Welded**

SPECIFICATIONS

FIXED STEEL LADDER							
WITHOUT CAGE				WITH CAGE			
Standard	Walk-Thru			Standard	Walk-Thru		
Tri-Arc Model #	Tri-Arc Model #	# of Rungs	Length top to bottom rung	Tri-Arc Model #	Tri-Arc Model #	# of Rungs	Length top to bottom rung
WLFS0104-Y	WLFS0204-Y	4	3'	WLFC1111-Y	WLFC1211-Y	11	10'
WLFS0105-Y	WLFS0205-Y	5	4'	WLFC1112-Y	WLFC1212-Y	12	11'
WLFS0106-Y	WLFS0206-Y	6	5'	WLFC1113-Y	WLFC1213-Y	13	12'
WLFS0107-Y	WLFS0207-Y	7	6'	WLFC1114-Y	WLFC1214-Y	14	13'
WLFS0108-Y	WLFS0208-Y	8	7'	WLFC1115-Y	WLFC1215-Y	15	14'
WLFS0109-Y	WLFS0209-Y	9	8'	WLFC1116-Y	WLFC1216-Y	16	15'
WLFS0110-Y	WLFS0210-Y	10	9'	WLFC1117-Y	WLFC1217-Y	17	16'
WLFS0111-Y	WLFS0211-Y	11	10'	WLFC1118-Y	WLFC1218-Y	18	17'
WLFS0112-Y	WLFS0212-Y	12	11'	WLFC1119-Y	WLFC1219-Y	19	18'
WLFS0113-Y	WLFS0213-Y	13	12'	WLFC1120-Y	WLFC1220-Y	20	19'
WLFS0114-Y	WLFS0214-Y	14	13'	WLFC1121-Y	WLFC1221-Y	21	20'
WLFS0115-Y	WLFS0215-Y	15	14'	WLFC1122-Y	WLFC1222-Y	22	21'
WLFS0116-Y	WLFS0216-Y	16	15'	WLFC1123-Y	WLFC1223-Y	23	22'
WLFS0117-Y	WLFS0217-Y	17	16'	WLFC1124-Y	WLFC1224-Y	24	23'
WLFS0118-Y	WLFS0218-Y	18	17'	WLFC1125-Y	WLFC1225-Y	25	24'
WLFS0119-Y	WLFS0219-Y	19	18'	WLFC1126-Y	WLFC1226-Y	26	25'
WLFS0120-Y	WLFS0220-Y	20	19'	WLFC1127-Y	WLFC1227-Y	27	26'
				WLFC1128-Y	WLFC1228-Y	28	27'
				WLFC1129-Y	WLFC1229-Y	29	28'
				WLFC1130-Y	WLFC1230-Y	30	29'
FIXED LADDER ACCESS RESTRICTION OPTIONS							
Guard Door closes off entry onto a fixed ladder. Cage Door closes off entry at bottom of cage.							
Guard Door				OPFS03-Y			
Cage Door				OPFS04-Y			