

## ONE STATION FLOOR MOUNTED SERVICE SINK WITH TUBULAR LEGS

### **TOE-PUSH OPERATED**







Item #:	_ Qty #:
Model #:	
Project #:	



#### **FEATURES:**

8 1/2" high backsplash.

12" sink bowl depth.

One stainless steel "Z" bracket supplied each unit.

One K-6 3 1/2" rear basket drain.

Four tubular stainless steel legs with stainless steel bullet feet. One stainless steel support shelf with rear turn-up.

**Toe-Push Operated:** Includes one **K-104** toe-push valve and one **K-121** spout.

Single hole provided.

#### **CONSTRUCTION:**

All TIG welded.

Welded areas blended to match adjacent surfaces and to a satin finish.

Die formed tubular wall brackets.

#### **MATERIAL:**

All 16 gauge type "304" stainless steel. 1 5/8" tubular "304" stainless steel legs. Stainless steel gussets.

#### **MECHANICAL:**

Single faucet holes.

		# 01	# OT		
Model #	Length	Spouts	Legs	Wt.	Cu.Ft.
FS-WM-2721FV	27"	1	4	82 lbs.	23



#### **MULTI-STATION ACCESSORIES & REPLACEMENT PARTS** Model Description QTY: **₩** K-6 3 1/2" Drain (1 1/2" I.P.S.) K-121 **K-06** Splash Mount Faucet Mounting Kit K-104 Stainless Steel Soap Dispenser (Wall Mount Only) **K-13** Toe-Push Valve Assembly **K-104** K-411 **K-121** Single Hole, Splash Mounted 3-1/2" Gooseneck Spout **K-411** Strainer Plate for 3-1/2" Drain Special Sizing Charge (Larger Size **K-508** TA-19 Cut Down To Smaller Size) **TA-19** Adjustable Stainless Steel Flanged Bullet Foot

Ships UPS

Standard Faucets conform to NSF 61 Standard 9 and compliance to AB 1953 Standards.

WARNING: Equipment that include faucets on this page may contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes: Email: smartfab@advancetabco.com or Fax: 631-586-2933 TOL ± .500" ALL DIMENSIONS ARE TYPICAL

# **FS-WM-2721FV** 2" 12" $21\frac{1}{2}$ 18" 12" 34" 12"-82 Lbs.

