

TINGLEY

est. 1896

HazProof® Steel Toe PR Safety Boot

Style Number - 82330

Compliance Standards: ASTM F2413 M/I/C PR EH*
NFPA 1990
ASTM F1671 Viral Penetration



Product Detail: Steel toe provides protection against toe impact and compression, and steel midsole provides puncture resistance. Steel shank provides firm arch support. Injection-molded construction for 100% liquidproof protection. Larger foot area is engineered to accommodate the extra bulk of an encapsulated suit, for comfortable fit.

*Electrical Hazard soles and heels are intended to reduce hazards due to accidental contact with live electrical circuits, electrically energized conductors, parts or apparatus. They are not intended for work environments where volatile chemicals or explosives may be present, where conductive footwear is required.

Warning: Electric Hazard features of the soles and heels will deteriorate in wet environments, and when worn with excessive wear on the soles and heels.

Product Type: Midcalf Boot

Insole: Closed cell EVA midsole for all day cushion comfort. Polyester felt insole added for additional comfort.

Sizes: US Men's 6 through 13
(size 13 accomodates up to Men's size 16)

Outsole Tread Pattern: Sure grip cleated outsole has excellent abrasion and slip resistance.

Color: Orange Upper / Ivory Outsole

Appearance: Boots are clean and free from obvious defects, flash and contamination. The surfaces are visually consistent in texture and contrast with no evidence of foreign material or distortion. Molded products are fully formed, well defined and properly aligned, with level outsoles, smooth seams and neatly trimmed edges. Colors are consistent within and between lots.

Material: Specially Blended PVC (polyvinyl chloride) with special chemical and permeation resistant compounds

Closure Type: Stretch fasteners (3)

Labeling: Date code, country of origin, and size are marked on the outsoles. Printed hangtag displays name, sku, UPC Code, and NFPA 1990 compliance. Boots are labeled to indicate compliance with ASTM F2413, NFPA 1990 and California Prop 65.

Packaging: Boots are pair packed in a clear plastic bag and labeled for individual sale. Packaged six (6) pairs per labeled, corrugated cardboard case.

Applications: Suited for various jobs within Chemical and Hazmat Cleanup.

Chemical Resistance: Hazardous Waste. See ASTM F1001 & MIL-STD-282 Listings.

Country of Origin: Mexico

Other: Testing and certification documents are available upon request from Tingley Rubber Corporation.

Dims & Weight by Size:	M6 W8	M7 W9	M8 W10	M9 W11	M10 W12	M11 W13	12	13
Height (in.)	11.0	11.0	11.3	11.3	11.3	11.5	11.5	11.5
Ball Width (in.)	4.4	4.6	4.7	4.7	4.8	4.8	4.8	4.9
Heel-to-Toe (in.)	11.8	12.1	12.4	12.8	13.1	13.4	13.7	14.1
Topline Circumference (in.)								
Weight (lbs)	6.0	6.2	6.6	6.8	7.1	7.5	7.7	7.9

Case Pack: 6 pairs

Package Dimensions:

		Case Carton (L x W x H)
Sizes 6 to 13		18 x 16 x 17 in