

TINGLEY

est. 1896

Pilot™ Safety Toe Puncture-Resistant Knee Boot

Style Number - 31341

Compliance Standards: ASTM F2413 M/IC PR EH*
ASTM F3445 SR



Product Detail: Steel toe provides protection against toe impact and compression. Flexible, puncture resistant steel midsole reduces risks from sharp objects. Injection molded seamless construction provides 100% liquidproof protection. Soft and flexible upper for all day working comfort. Slip resistant per ASTM F3445, the standard specification as of July 2021.

**Electrical Hazard soles and heels are intended to reduce the hazards due to accidental contact with live electrical circuits, electrically energized conductors, parts or apparatus. Electric Hazard soles and heels are not intended for wear in those work environments where volatile chemicals or explosives may be present, where conductive footwear is required.*

Warning: Electric Hazard features of the soles and heels will deteriorate in wet environments, and when worn with excessive wear on the soles and heels.

Product Type: Knee Boot

Insole: Removable contour insole wicks sweat to keep feet dry and comfortable.

Sizes: US Men's 4 through 14

Outsole Tread Pattern: Cleated outsole spits out debris for excellent gripping action.

Color: Black Upper / Black Outsole

Appearance: Boots are clean and free from obvious defects, flash and contamination. The surfaces are visually consistent in texture and contrast with no evidence of foreign material or distortion. Molded products are fully formed, well defined and properly aligned, with level outsoles, smooth seams and neatly trimmed edges. Colors are consistent within and between lots.

Material: Enhanced Quality PVC (polyvinyl chloride)

Closure Type: None

Labeling: Lot code, country of origin, and size are marked on the outsoles. Boots are labeled to indicate compliance with ASTM F2413, F3445 and California Prop 65.

Packaging: Boots are pair packed with a plastic fastener strung through a pre-punched hole in the hangtag. Packaged six (6) pairs per labeled, corrugated cardboard case.

Applications: Suited for various jobs within Construction, Agriculture, Industry, Foul Weather and General Purpose.

Chemical Resistance: Certain acids and alkalies, fats, oils, hydrocarbons and other chemicals.

Country of Origin: China

Other: Testing and certification documents are available upon request from Tingley Rubber Corporation.

Dims & Weight by Size:	M4 W6	M5 W7	M6 W8	M7 W9	M8 W10	M9 W11	M10 W12	M11 W13
Height (in.)	14.3	14.5	14.7	14.9	15.1	15.3	15.6	15.8
Ball Width (in.)	3.9	3.9	4.0	4.1	4.2	4.3	4.3	4.4
Heel-to-Toe (in.)	10.2	10.5	10.8	11.0	11.6	11.7	12.0	12.4
Topline Circumference (in.)	16.5	16.9	17.3	17.6	17.9	18.2	18.6	19.0
Weight (lbs)	4.4	4.6	5.1	5.3	5.3	5.7	6.2	6.4

Dims & Weight by Size:	12	13	14
Height (in.)	16.0	16.1	16.2
Ball Width (in.)	4.5	4.6	4.7
Heel-to-Toe (in.)	12.7	13.2	13.4
Topline Circumference (in.)	19.4	19.7	20.0
Weight (lbs)	6.6	6.8	7.1

Case Pack: 6 pairs

Package Dimensions:

	Case Carton (L x W x H)
Sizes 4 to 5	17 x 16 x 12 in
Sizes 6 to 8	17 x 17 x 12 in
Sizes 9 to 11	19 x 19 x 13 in
Sizes 12 to 14	20 x 19 x 13 in