

| Model: | Item #: | Date: |
|--------|---------|-------|
| | | |

Project:_____ Qty:____ Approved By:_____

Gas Connector Kit 9

Gas Connectors



Includes:

| No. | Name | Description |
|-----|--------------------------|---|
| 1 | Gas Connector | For stationary and caster-mounted kitchen equipment. |
| 2 | Quick Disconnect | Easily disconnects gas hose to move equipment for maintenance and cleaning. |
| 3 | Shut-off Valve | Required by code to allow manual shutoff within 6 ft. of appliance. |
| 4 | Restraining Cable Kit | Prevents hose from being pulled too far. Includes mounting hardware. |
| 5 | (2) 90° Elbows | Gives versatility during installation. |
| 6 | SwivelKing [™] | Stainless steel construction with dual 360° rotation significantly reduces stress |

Visit krowne.com for complete replacement parts.

Product Compliance

- ANSI Z21.41-2014 CSA 6.9-2014 Quick Disconnect Devices For Use With Gas Fuel Appliances
- ANSI Z21.69-2009 CSA 6.16-2009 Connectors
 For Moveable Gas Appliances
- ANSI Z21.69a-2012 CSA 6.16a-2012 Addenda

Standard Features

- For use with stationary and caster-mounted commercial kitchen equipment
- Male NPT End fittings rotate 360
- Heavy duty stainless steel corrugated tubing for flexibility
- Heavy duty stainless steel radial wrap prevents hose from stretching
- PVC Protective coating with anti-microbial agent for easy cleaning
- Welded construction for added durability
- For Indoor Use Only

Specifications

| Pressure | ■ 1/2 psi | |
|--------------|-------------------------------|--|
| End Fittings | ■ Carbon Steel, Chrome Plated | |
| Tubing | ■ Stainless Steel 304 | |
| Braiding | ■ Stainless Steel 304 | |

| Model No. | Interior Size | Length | BTU/hr |
|-----------|---------------|--------|--------|
| M5024K9 | 1/2" | 24" | 87K |
| M5036K9 | 1/2" | 36" | 77K |
| M5048K9 | 1/2" | 48" | 68K |
| M5060K9 | 1/2" | 60" | 60K |
| M5072K9 | 1/2" | 72" | 55K |
| M7524K9 | 3/4" | 24" | 232K |
| M7536K9 | 3/4" | 36" | 218K |
| M7548K9 | 3/4" | 48" | 180K |
| M7560K9 | 3/4" | 60" | 158K |
| M7572K9 | 3/4" | 72" | 139K |
| M10024K9 | 1" | 24" | 414K |
| M10036K9 | 1" | 36" | 379K |
| M10048K9 | 1" | 48" | 334K |
| M10060K9 | 1" | 60" | 294K |
| M10072K9 | 1" | 72" | 279K |
| M12524K9 | 1-1/4" | 24" | 699K |
| M12536K9 | 1-1/4" | 36" | 615K |
| M12548K9 | 1-1/4" | 48" | 541K |
| M12560K9 | 1-1/4" | 60" | 476K |
| M12572K9 | 1-1/4" | 72" | 419K |
| | | | |

WARNING: Restraining Kits are required by law for all moveable gas equipment California Proposition 65 Warning

