	Project Name:			AIA#:
Model #:		Location:		
		tom #·	Quantity:	



Globe 60 Quart Planetary Floor **Mixer with Power Bowl Lift**

Enhanced to handle a variety of mixes!

Utilizing 4 speeds, operator-friendly power bowl lift and front-mounted touch pad control panel with digital timer and heavy duty transmission.









Model

□ SP62P-4

Standard Features

- Powerful 3 HP fixed speed custom built motor
- Direct gear-driven, high-torque transmission
- Heat-treated hardened steel alloy gears and shafts
- Four fixed speeds
- Handles up to 50 lbs. of flour (80 lb. batch size)
- Safety interlocked power bowl lift
- Permanently lubricated oil bath transmission
- Thermal overload protection
- Front-mounted touch pad controls with 60-minute digital timer and last-batch recall
- Stainless steel, interlocking bowl guard with built-in, fully welded ingredient chute
- Heavy duty bowl truck (pictured)
- Rigid cast iron body
- Industry standard #12 attachment hub
- NSF approved enamel gray paint
- 6-foot cord and ground plug
- Auto shut off, for improved protection of motor and transmission protection

Standard Accessories/Attachments

- 60 qt stainless steel bowl (#304 series)
- Aluminum spiral dough hook, flat beater and stainless steel whip
- Non-slip rubber feet
- Bowl truck

Warranty


Two years parts and labor


Optional Attachments/Accessories

- Slicer/shredder/grater for #12 hub
- Meat grinder for #12 hub
- **Bowl Scraper**
- Additional bowl truck
- Correctional package
- Extended warranty

To select options see back

Approved by:	Date:
• • •	





SPECIFICATIONS											
Model	Motor	Volts	Amps	Transmission Type	Capacity	Controls	Power Bowl Lift	Agitator Speeds (RPMs)		Attachment Speeds (RPMs)	
Wodei	WIOTOI							First	Second	First	Second
SP62P-4 (1 Phase)	3 HP	220/60/1	18	Gear	60 qt / 57 liter	Digital, front	1/8 HP Motor	60	105	67	118
SP62P-4	3 HP	208/60/3	12	Gear	60 qt / 57 liter	mounted		Third	Fourth	Third	Fourth
(3 Phase)	з пР							176	310	198	349

Cord & Plug: Attached 6-foot flexible 3-wire cord with molded plug fits a grounded receptacle. Single phase NEMA L6-20P (1) Three phase NEMA L15-20P (1) *Specify voltage when ordering.

DIMENSIONS | SHIPPING INFORMATION

Reinforced carton for shipping. The weight and dimensions of this reinforced carton are included below and may vary from shipment to shipment. This product ships on a pallet. Freight class 85.

	- F F			
Model	Overall Dimensions	Net Weight	Shipping Dimensions	Shipping Weight
SP62P-4	30.25" w x 41.6" d x 60" h (76.83 cm x 105.66 cm x 152.4 cm)	980 lbs (444 kg)	48" w x 48" d x 76" h (122 cm x 122 cm x 193 cm)	1,228 lbs (556 kg)

Mixer is constructed of a rigid cast iron body with front-mounted controls, and 60-minute digital timer. Mixer has 3 HP custom built motor with overload protection and direct gear-driven, high torque permanently lubricated 4 speed transmission consisting of heat-treated hardened steel alloy gears and shafts. Mixer comes with 60 gt. stainless steel bowl, aluminum bowl truck and stainless steel wire whip, aluminum dough hook and non-slip rubber feet. Interlocked with stainless steel bowl guard with fully welded ingredient chute. Mixer has #12 attachment hub and interlocked power bowl lift. Mixer is NSF and ETL listed. Two year parts and labor warranty.

OPTIONAL MIXER ACCESSORIES AND HUB ATTACHMENTS

- **XXBOWL-62** 60 qt. stainless steel (S/S) bowl
- ☐ XXBEAT-62 Alum. flat beater
- ☐ XXHOOK-62 Alum. dough hook
- ☐ XXWHIP-62 S/S wire whip
- ☐ XBTRUCK-62 Heavy-duty bowl truck

HUB:

- XVSGH 9" Slicer/Shredder/Grater housing only (no plates included-must select from plates listed on this sheet)
- ☐ XASP Adjustable slicing plate (for vegetables only)
- ☐ **XPH** Plate holder

- Shredding Plates:
- ☐ XSP332* 3/32" (2.3 mm)☐ XSP316* 3/16" (4.7 mm)
- ☐ XSP14* 1/4" (6.3 mm)
- **☐ XSP516*** 5/16" (7.9 mm) **☐ XSP12*** 1/2" (12.7 mm)
- ☐ XGP* Grating plate
- *Only 1 plate holder required ☐ XMCA-SS Meat grinder assembly
- (Polished stainless steel cylinder, worm gear, ring, and s/s pan. Includes knife, 3/16" plate, and pusher.)
- **XXCK** Chopper knife for XMCA-SS

Chopper Plate Sizes Available:

- **☐ CP02-12** 1/16" (2 mm) ☐ CP04-12 5/32" (4 mm)
- ☐ CP05-12 3/16" (5 mm) (6 mm)
- ☐ CP06-12 1/4" ☐ CP08-12 5/16" (8 mm) ☐ CP10-12 3/8" (10 mm)
- ☐ CP12-12 1/2" (12 mm)**CP14-12** 9/16" (14 mm)
- **□ CP16-12** 5/8" (16 mm) **CP18-12** 11/16" (18 mm)
- ☐ CP00-12 Stuffing plate ☐ XST12 1/2" Stuffing tube (mutton)
- ☐ XST34 3/4" Stuffing tube (pork)

☐ FACTORY INSTALLED OPTION:

XXCORR-62 Correctional package, includes tamper resistant external fasteners.

☐ EXTENDED WARRANTY SP-XDSPL Extended warranty for SP62P mixer, extends factory warranty to 3-years. Available only at time of purchase.