

PROJECT:		
ITEM#		QTY:
MODEL#		
AIA #	SIS #	
APPROVED	i	

HORIZON TOP MOUNT FREEZERS

Model: HF3HC-1HG

HALF GLASS DOOR



7 YEAR WARRANTY Parts, Labor, and Compressor

CABINET CONSTRUCTION

- Exterior is stainless steel front and continuous coil coated sides
- · Interior liner is made of corrosion resistant aluminum
- · Full electronic control
- Expansion valve technology
- · One piece grille
- · LED interior light
- Self-closing door with 120° stay-open feature, on cam-lift hinges
- · Snap-in magnetic gaskets for positive door seal
- Nine (9) heavy-duty epoxy coated wire shelves
- · 6" Heavy-duty casters, two (2) with brakes
- 8' Cord and plug (see electrical data for details)

OPTIONS & ACCESSORIES

- Tray slide pair, 1 tray slide set for (1) 18" x 26" or (2) 14" x 18" pans (A)
- Stainless steel universal tray slide pair, 1 tray slide set for (1) 18" x 26" or (2) 14" x 18" pans (AC)
- Tray slide kit #4 (19 sets per half section)
- · Additional epoxy shelves
- · Shelf clips
- · Door locks
- Stainless steel breaker
- · 6" Legs seismic/flanged
- 3" Casters
- Remote option* (see note on back page)

REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- Hot gas condensate evaporator
- · Adaptive defrost
- · Epoxy coated evaporator coil
- Freezer capable of maintaining product temperature down to -10°F


BEVERAGE-AIR.

Horizon Top Mount Model: HF3HC-1HG

PLAN VIEW

74" INTERNAL WIDTH

ELEVATION VIEW



SIDE VIEW

	-	33 5/8" OVERALL DEPTH -
62" NTERNAL HEIGHT		
-		25 7/8" INTERNAL DEPTH

EXTERNAL DIMENSIONAL DATA			
Width Overall (in)	78"		
Depth Overall (in)	33 5/8"		
Height Overall (in)	85"		
Number of Doors	6		
Depth with Door Open 90° (in)	55 1/8"		
Door Openings (in)	21 5/8" x 29 5/8"		
INTERNAL DIMENSIONAL DATA			
NET Capacity (cubic ft).	69.1		
Internal Width Overall (in)	74"		
Internal Depth Overall (in)	25 7/8"		
Internal Height Overall (in)	62"		
Number of Shelves	9		

*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.

We reserve the right to change specifications and product design without $% \left(1\right) =\left(1\right) \left(1\right) \left$ notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM).

ELECTRICAL DATA				
Full Load Amps	15.3			
Voltage	115/60/1			
Nema Plug (8' cord)	5-20P			
REFRIGERATION DATA				
Horsepower	(2) 3/4			
Capacity (BTU/Hr)	3854			
Heat Rejection (BTU/Hr)	5781			
Charge (lbs/grams/ounces)	0.2866 / 130 / 4.59			
SHIPPING DATA				
Gross Weight - Crated	745 lbs.			
Height - Crated (in)	88"			
Width - Crated (in)	80"			
Depth - Crated (in)	41"			

ELECTRICAL CONNECTION



115/60/1

Unit pre-wired at factory and include 8' long cord NEMA 5-20P and plug set.

3779 Champion Blvd., Winston-Salem, NC 27105 | 888-845-9800 | Fax: 336-245-6453 | Beverage-Air.com | Sales@bevair.com

Date Issued 12/25 | Printed in U.S.A.

