

TPI Industrial Specialty Circulator Heads

8



Intertek

*Listing applies to
277V models only

WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.

Features

- No cord-junction box provided for hard wiring
- Steel hub/spider aluminum paddle blades
- Coated steel guards
- Meets OSHA standards
- 1 year limited warranty
- Made in U.S.A. with domestic and foreign components

Motor Specifications

- All 1 Speed (except 277V which is 2 Speed)
- Totally enclosed, permanently lubricated
- Ball bearing

Standard Models

GENERAL DESCRIPTION	MFG MODEL NUMBER	MFG CATALOG NUMBER	SIZE	CFM*		VELOCITY PROFILE CFM / Area Sq Ft	MOTOR			AMPS (HIGH)					WT. (LBS)	LIST
				HIGH	LOW		HP	RPM	VOLTS	120v 1 ph	240v 1 ph	277v 1 ph	240v 3 ph	480v 3 ph		
Hazardous Location Class I Group D Class II Group F & G Unassembled Head	ACH 24-EX1	08551902	24"	4300		6000 / 240	1/4	1725	120 or 240 1-phase	5	2.6	----	----	----	66	1267
	ACH 30-EX1	08552002	30"	5400		7200 / 250									69	1374
	ACH 24-EX3	08552102	24"	4300		6000 / 240									66	1351
	ACH 30-EX3	08552202	30"	5400		7200 / 250							1.4	0.7	69	1479
240V / 480V 3-Phase Unassembled Head	ACH 24-TE3	08552302	24"	4300		6000 / 240	1/4	1725	240 or 480 3-phase	----	----		1.4	0.7	45	874
	ACH 30-TE3	08552402	30"	5400		7200 / 250									48	894
277 Volt Assembled Head	IHP 24-H-277	08541302	24"	4300	3900	6000 / 240	1/3	1125	277 1-phase	----	----	1	----	----	40	614
	IHP 30-H-277	08542202	30"	5400	4700	7200 / 250									44	653
Wash down rated 120V / 240V 1-Phase Assembled Head	IHP 20-H-WD	08721902	20"	3200		5200 / 220	1/3	1725	120 or 240 1-phase	4.5	2.2		----	----	46	1168
	IHP 24-H-WD	08541802	24"	4300		6000 / 240									48	1210
	IHP 30-H-WD	08541902	30"	5400		7200 / 250									52	1251


*Measured 2 feet from face of fan

Note: Wash down rated fan heads have heavy zinc coated guards - Use FDA white coated mounts shown on page 7 for food service applications

Product Specifications

- Pedestal pole adjusts the center of fan from 48" to 67" and bolts to 27" diameter steel dome base with 5 bolts
- I-beam mount & ceiling mount require 1 1/2" or longer pipe nipple for assembly (not supplied)
- Pole mount attaches to 4", 6", or 8" with U-bolts (not supplied)

Standard Models



CIRCULATOR MOUNT	MFG MODEL NUMBER	MFG CATALOG NUMBER	WT. (LBS)	LIST
Pedestal	ACM-P	07961802	34	225
Wall Mount	ACM-W	07961902	3	87
I-Beam Mount	ACM-I	07962002	9	170
Ceiling Mount	ACM-C	07962102	3	112
Suspension Mount	ACM-S	07962202	2	77
Pole Mount	ACM-PM	08681802	5	124
Optional Wheel Kit	ACM-WK	08681302	4	105