



# KM-2200S\_J3

## 3 PHASE STACKABLE ICE CUBER



KM-2200S\_J3  
05/31/17  
Item # 13061

W x D x H  
48" x 27<sup>3/8</sup>" x 36<sup>7/16</sup>"

**KM Edge**  
DESIGN

### KM-2200SWJ3

Water-Cooled 3 Phase  
Shown on optional bin: B-900

### KM-2200SRJ3 ★

Remote Air-Cooled 3 Phase





Item #: \_\_\_\_\_  
Project: \_\_\_\_\_  
Qty: \_\_\_\_\_  
AIA#: \_\_\_\_\_

## Features

► Individual crescent cube

► Stainless steel evaporator

► CycleSaver™ design 

- Up to 2221 lbs. of ice production per 24 hours
- Stackable for 4442 lbs. per 24 hours ice production in the same floor space
- Durable stainless steel exterior
- Protected by H-Guard Plus Antimicrobial Agent 
- EverCheck™ alert system 
- R-404A Refrigerant

### Available on Bins:


B-800 B-1150SS B-1500SS Top kit may be required.  
B-900 B-1300SS B-1650SS See Bin Spec Sheets.

### Warranty:

Valid in United States, Canada, Puerto Rico and U.S. Territories.  
Contact factory for warranty in other countries.

Condenser	Model	ICE PRODUCTION		WATER USAGE		ELECTRICAL							Shipping Weight	ENERGY STAR®
		Air / Water Temp Lbs. per 24 hours		Per Cycle		Potable Gal. per 100 lbs.	Condenser Gal. per 100 lbs.	kWh Used per 100 lbs.	Max. Fuse Size or HACR Circuit Breaker	Amperage	Voltage	Heat Rejection BTU/hr.		
		70°/50°F	90°/70°F	Lbs.	Cubes	90°/70°F	90°/70°F	90°/70°F						
3 Phase	Water-Cooled	KM-2200SWJ3	2221	2200	42.7	2160	15.0	95	3.11	30A	12.8A	208-230V/60/3	27,200	440 lbs.
	Remote Air-Cooled	KM-2200SRJ3	2206	2075	43	2160	15.0	N/A	3.75	20A	15.9A	208-230V/60/3	26,700	440 lbs. ★

## KM Edge Cube Dimensions\*



\* approximate size in inches, image not to scale

## Operating Limits

- Ambient Temp Range 45 - 100°F
- Water Temp Range 45 - 90°F
- Water Pressure 10 - 113 PSIG
- Voltage Range 187 - 253V

## Service

- Panels easily removed and all components accessible for service.
- Allow 6" (15 cm) clearance at rear, sides, and top for proper air circulation and ease of maintenance/service.

## Plumbing

- Icemaker Water Supply Line: Minimum 3/8" Nominal ID Copper Water Tubing or Equivalent
- Icemaker Drain Line: Minimum 3/4" Nominal ID Hard Pipe or Equivalent
- Water-Cooled Model (Lines Must Be Independent of Icemaker)
- Condenser Water Supply Line: Minimum 3/8" Nominal ID Copper Water Tubing or Equivalent
- Condenser Drain/Return Line: Minimum 3/8" Nominal ID Hard Pipe (open drain system) or Copper Water Tubing (closed loop system) or Equivalent




# KM-2200S\_J3

## 3 PHASE STACKABLE ICE CUBER




KM-2200S\_J3  
05/31/17  
Item # 13061

FRONT VIEW




WATER-COOLED




REMOTE AIR-COOLED

SIDE VIEW




WATER-COOLED




REMOTE AIR-COOLED

REAR VIEW




WATER-COOLED




REMOTE AIR-COOLED

BOTTOM VIEW



WATER-COOLED



REMOTE AIR-COOLED

**URC-22F Remote Condenser (Sold Separately)**  
(W x D x H) 46<sup>3/8</sup> X 14<sup>1/16</sup> X 40<sup>1/2</sup>  
For Use with KM-2200SRJ3



**Pre-Charged Tubing Kits**  
(Sold Separately)  
20' R404-20610  
35' R404-35610  
55' R404-55610

Voltage supply for the URC Remote Condenser is supplied from the Ice Maker. No additional circuit is required.

