



Lavex

Item #: 25019154553ID Project: \_\_\_\_\_

Qty: \_\_\_\_\_ Date: \_\_\_\_\_ Approval: \_\_\_\_\_

**Lavex 18" x 5' 24V Powered Roller Conveyor with 3 Roller Zones, 4 1/2" Centers, and Power Supply - 120V**

Item #25019154553ID



**Technical Data**

Length	5 Feet
Width	18 Inches
Height	20 - 26 Inches
Roller Center Width	4 1/2 Inches
Voltage	120 Volts
Color	Blue Silver
Conveyor Speed	50 - 190 Feet Per Minute
Features	Adjustable Legs
Frame Material	Powder-Coated Steel

**Features**

- Durable 10 gauge steel frame with a blue powder-coated finish
- Operates using 24V DC motorized rollers with 3 individual control zones
- Features 1 15/16" diameter rollers on 4 1/2" centers
- Legs adjust from 20" to 26" high to create your ideal working height
- Includes a mounted 120V power supply for quick and easy setup

**Certifications**





## Technical Data

Gauge	10 Gauge
Number of Control Zones	3 Zones
Plug Type	NEMA 5-15P
Power Type	Electric
Roller Material	Galvanized Steel
Style	Roller Conveyor
Type	Motorized Conveyors

## Notes & Details

Upgrade your material handling system with this Lavex powered conveyor. This motorized unit features a space-saving design, and it allows multiple lines to be tiered up to take up less vertical space. It operates using 24V DC motorized rollers with 3 individual control zones, allowing you to move product along the conveyor one zone at a time. This design also includes photo-eye sensors to start and stop the conveyor automatically. Each zone features a maximum load rating of 110 lb.

This unit offers quiet operation for nondisruptive use. It features an ample 5' length with a usable width of 15" between the frames to transport product. It has 1 15/16" diameter rollers constructed of 16 gauge, galvanized floor-coat steel, ensuring it can withstand frequent use in your industrial facility. These rollers have 4 1/2" centers between each. An O-ring style drive belt connects each roller in the zone to the motor.

This durable conveyor boasts a 10 gauge steel frame with a blue powder-coated finish. For additional versatility, it features stationary, adjustable support legs. These legs adjust from 20" to 26" high, allowing you to create the perfect working height for your facility. This unit comes complete with a mounted 120V power supply for quick and easy setup.

**⚠ WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).