

In the Box

- Power cord(s)
- Software and Documentation CD
- Photoconductor unit
- 4 Developer units (K, C M, Y)
- 3,000\*-page Black Toner Cartridge
- 2,000\*-page Color (CMY) Toner Cartridges
- Lexmark CS622de color laser printer
- Lexmark Cartridge Collection Program information
- Statement of limited warranty / guarantee
- Setup guide or sheet (network and local attachment)

Box contents may vary by country and/or reseller. Subject to change without notice.

Ethernet, USB or parallel cable not included.

\*Average continuous black or continuous composite CMY declared cartridge yield in one-sided (simplex) mode up to this number of standard pages in accordance with ISO/IEC 19798.

General Specs

Part #	42C0080
Print Technology	<ul style="list-style-type: none"><li>• Color Laser</li></ul>
Workgroup Size	<ul style="list-style-type: none"><li>• Small-Medium Workgroup</li></ul>
Display	<ul style="list-style-type: none"><li>• Lexmark e-Task 4.3-inch (10.9 cm) color touch screen</li></ul>
Media Sizes Supported	<ul style="list-style-type: none"><li>• A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Hagaki Card, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope</li></ul>

<b>Included Paper Handling</b>	<ul style="list-style-type: none"> <li>Integrated Duplex, Single-Sheet Manual Feed, 125-Sheet Output Bin, 250-Sheet Input</li> </ul>
<b>Standard Ports</b>	<ul style="list-style-type: none"> <li>Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), USB 2.0 Specification Hi-Speed Certified (Type B)</li> </ul>
<b>Size (in. - H x W x D)</b>	<ul style="list-style-type: none"> <li>12.1 x 17.4 x 16.6 in.</li> </ul>
<b>Weight (lb.)</b>	<ul style="list-style-type: none"> <li>46 lb.</li> </ul>
<b>Packaged Size (in. - H x W x D)</b>	<ul style="list-style-type: none"> <li>15.8 x 19.5 x 23.4 in.</li> </ul>
<b>Packaged Weight (lb.)</b>	<ul style="list-style-type: none"> <li>52.5 lb.</li> </ul>

## Printing

<b>Print Speed</b>	<ul style="list-style-type: none"> <li>Up to:</li> <li>Black: 40 ppm<sup>1</sup> (Letter)</li> <li>Color: 40 ppm<sup>1</sup> (Letter)</li> </ul>
<b>Print Speed Duplex</b>	<ul style="list-style-type: none"> <li>Up to:</li> <li>Black: 20 spm<sup>1</sup> (Letter)</li> <li>Color: 20 spm<sup>1</sup> (Letter)</li> </ul>
<b>Time to First Page</b>	<ul style="list-style-type: none"> <li>As fast as:</li> <li>Black: &lt; 7 seconds</li> <li>Color: &lt; 7 seconds</li> </ul>
<b>Print Resolution</b>	<ul style="list-style-type: none"> <li>Black: 1200 x 1200 dpi, 4800 CQ (2400 x 600 dpi)</li> <li>Color: 4800 CQ (2400 x 600 dpi), 1200 x 1200 dpi</li> </ul>
<b>Duplex</b>	<ul style="list-style-type: none"> <li>2-sided:</li> <li>Integrated Duplex</li> </ul>
<b>Printable Area</b>	<ul style="list-style-type: none"> <li>0.17 inches of the top, bottom, right and left edges (within)</li> </ul>

---

## Paper Handling

<b>Media Types Supported</b>	<ul style="list-style-type: none"><li>• Vinyl Labels, Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper &amp; Specialty Media Guide</li></ul>
<b>Finishing Option</b>	<ul style="list-style-type: none"><li>• No</li></ul>
<b>Number of Paper Inputs</b>	<ul style="list-style-type: none"><li>• Standard: 2</li><li>• Maximum: 5</li></ul>
<b>Paper Input Capacity</b>	<ul style="list-style-type: none"><li>• Standard: 250+1 pages 20 lb or 75 gsm bond</li><li>• Maximum: 1450+1 pages 20 lb or 75 gsm bond</li><li>• 250+1 pages 20 lb or 75 gsm bond</li></ul>
<b>Paper Output Capacity</b>	<ul style="list-style-type: none"><li>• Up to:</li><li>• Standard: 125 pages 20 lb or 75 gsm bond</li><li>• Maximum: 125 pages 20 lb or 75 gsm bond</li></ul>
<b>Paper Weight Range Supported</b>	<ul style="list-style-type: none"><li>• lb.:</li><li>• 16 - 53 lb. (Standard Tray)</li></ul>
<b>Integrated Tray Card Stock Upper limit</b>	<ul style="list-style-type: none"><li>• Cover - 216 gsm (74 lb) (grain long)</li><li>• Index Bristol - 200 gsm (110 lb) (grain long)</li><li>• Tag -200 gsm (122 lb) (grain long)</li></ul>
<b>Optional Paper Handling</b>	<ul style="list-style-type: none"><li>• 650-Sheet Duo Tray, 550-Sheet Tray</li></ul>
<b>Recommended Monthly Page Volume</b>	<ul style="list-style-type: none"><li>• 1500 - 10000 pages<sup>2</sup></li></ul>
<b>Maximum Monthly Duty Cycle</b>	<ul style="list-style-type: none"><li>• Up to:</li><li>• 100000 pages per month<sup>3</sup></li></ul>

---

## Cartridges & Imaging

### Laser Cartridge Yields

- up to:
- 1,400<sup>4</sup>-page Color (CMY) Cartridges
- 2,000<sup>4</sup>-page Black Cartridge
- 5,000<sup>4</sup>-page Color (CMY) Extra High Yield Cartridges
- 8,500<sup>4</sup>-page Black Extra High Yield Cartridge
- 7,000<sup>4</sup>-page Color (CMY) Ultra High Yield Cartridges
- 10,500<sup>4</sup>-page Black Ultra High Yield Cartridge

---

### Cartridge(s) Shipping with Product

- 3,000<sup>4</sup>-page Black Return Program Toner Cartridge<sup>4</sup>, 2,000<sup>4</sup>-page Color (CMY) Return Program Toner Cartridges<sup>4</sup>

---

### Replacement Cartridges:

- Product functions only with replacement cartridges designed for use in a specific geographical region. See [www.lexmark.com/regions](http://www.lexmark.com/regions) for more details.
- 

## Hardware

### Processor Speed

- Dual Core, 1.0 GHz

---

### Memory

- Standard: 1024 MB
- Maximum: 1024 MB

---

### Hard Disk

- Option available

---

### Printer Languages

- Standard:
- PCL 5c Emulation, PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, PDF 1.7 emulation, Direct Image, AirPrint™

---

### Fonts and Symbol Sets

- 2 PCL bitmap fonts, 158 scalable PostScript fonts, OCR-A, OCR-B scalable PCL 5e fonts, For more information, refer to the Technical Reference., 84 scalable PCL fonts, 3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 5 PPDS bitmap fonts, 39 scalable PPDS fonts

<b>Touch Screen Display</b>	<ul style="list-style-type: none"> <li>• Yes</li> </ul>
<hr/>	
Connectivity	
<b>Direct USB</b>	<ul style="list-style-type: none"> <li>• Yes</li> </ul>
<b>Ethernet Network</b>	<ul style="list-style-type: none"> <li>• Yes</li> </ul>
<b>Network Protocol Support</b>	<ul style="list-style-type: none"> <li>• TCP/IP IPv6, TCP/IP IPv4, TCP, UDP</li> </ul>
<b>Network Printing Methods</b>	<ul style="list-style-type: none"> <li>• LPR/LPD, Direct IP (Port 9100), Telnet, FTP, TFTP, Enhanced IP (Port 9400), ThinPrint .print integration, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol)</li> </ul>
<b>Network Management Protocols</b>	<ul style="list-style-type: none"> <li>• DHCP<sup>5</sup>, APIPA (AutoIP)<sup>5</sup>, mDNS<sup>5</sup>, IGMP<sup>5</sup>, Bonjour<sup>5</sup>, WINS<sup>5</sup>, DDNS<sup>5</sup>, SNMPv3<sup>5</sup>, SNMPv1, SNMPv2c<sup>5</sup>, Telnet<sup>5</sup>, NTP<sup>5</sup>, ICMP<sup>5</sup>, HTTP<sup>5</sup>, DNS<sup>5</sup>, ARP<sup>5</sup>, HTTPs (SSL<sup>5</sup>/TLS)<sup>5</sup>, Finger<sup>5</sup></li> </ul>
<b>Network Security</b>	<ul style="list-style-type: none"> <li>• IPSec, SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS</li> </ul>
<b>Optional Network Ports</b>	<ul style="list-style-type: none"> <li>• Marknet N8372 WiFi Option</li> </ul>
<hr/>	
Supported Operating Systems	
<b>Microsoft Windows Operating Systems Supported</b>	<ul style="list-style-type: none"> <li>• Windows 10, Windows 8.1, Windows 8, Windows 8 x64, Windows 7 x64, Windows 8.1 x64, Windows 7</li> </ul>
<b>Apple Operating Systems Supported</b>	<ul style="list-style-type: none"> <li>• Apple OS X (10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13)</li> </ul>
<b>Linux Operating Systems Supported</b>	<ul style="list-style-type: none"> <li>• Debian GNU/Linux 7.0, 8.0, openSUSE 13.1, 13.2, Ubuntu 16.04 LTS, Fedora 23, 24, openSUSE Linux 42.3, Red Hat Enterprise Linux WS 6, 7, SUSE Linux Enterprise Server 10, 11, 12</li> </ul>
<b>Citrix MetaFrame</b>	<ul style="list-style-type: none"> <li>• Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows Server 2012 with Citrix XenApp 6.0, 6.5, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0</li> </ul>

<b>Novell Operating Systems Supported</b>	<ul style="list-style-type: none"> <li>Novell Open Enterprise Server on SUSE Linux Enterprise Server, Novell NetWare 5.1(SP 6+), 6.0(SP 3+) with Novell Distributed Print Services (NDPS), Novell Open Enterprise Server 2 SP2 on SuSE Linux Enterprise Server 10 SP3 3, Novell NetWare 6.5 Open Enterprise Server, Novell Open Enterprise Server 11 on SUSE Linux Enterprise Server 11, Novell Open Enterprise Server 2 on SUSE Linux Enterprise Server 10 SP4</li> </ul>
<b>UNIX Operating Systems Supported</b>	<ul style="list-style-type: none"> <li>Sun Solaris x86 10, 11, Sun Solaris SPARC 10, 11, IBM AIX 6.1, 7.1</li> </ul>
Electrical & Operation	
<b>ENERGY STAR</b>	<ul style="list-style-type: none"> <li>Yes</li> </ul>
<b>ENERGY STAR Typical Electricity Consumption</b>	<ul style="list-style-type: none"> <li>TEC:</li> <li>0.57 kilowatt-hours per week</li> </ul>
<b>Noise Level</b>	<ul style="list-style-type: none"> <li>Operating:</li> <li>Inaudible dBA (Idle)</li> <li>51 dBA (Print)</li> </ul>
<b>Duplex Print Noise Level</b>	<ul style="list-style-type: none"> <li>Operating:</li> <li>53 dBA</li> </ul>
<b>Average Power</b>	<ul style="list-style-type: none"> <li>0.2 watts (Hibernate Mode)</li> <li>1.42 watts (Sleep Mode)</li> <li>37 watts (Ready Mode)</li> <li>570 watts (Printing)</li> </ul>
<b>Specified Operating Environment</b>	<ul style="list-style-type: none"> <li>Humidity: 8 to 80% Relative Humidity</li> <li>Altitude: 0 - 3048 Meters (10,000 Feet)</li> <li>Temperature: 10 to 32°C (50 to 90°F)</li> </ul>
<b>Product Certifications</b>	<ul style="list-style-type: none"> <li>ENERGY STAR, Blue Angel RAL-UZ 205, ICES-003 Class A, BSMI Class A, VCCI Class A, US FDA, UL 60950-1, FCC Class A, cUL CAN/CSA-C22.2 60950-1, CB EN/IEC 60950-1, CB</li> </ul>

	EN/IEC 60825-1, CE DoC (EN 62301 Class A, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class A, EN 55024, UL), EFTA (CE), KCC, CCC, CECP, CEL, C-tick DoC, UL-AR, KC mark, UL GS mark, UCRF, EC 1275, China Green Product (CGP)
<b>UNSPSC Code</b>	<ul style="list-style-type: none"> <li>43212105</li> </ul>
<b>Harmonized Tariff Code</b>	<ul style="list-style-type: none"> <li>8443.32.1010</li> </ul>
<b>Country of Origin</b>	<ul style="list-style-type: none"> <li>China (PRC)</li> </ul>
<b>License/Agreement Terms</b>	<ul style="list-style-type: none"> <li>Printers are sold subject to certain license/agreement conditions. See <a href="http://www.lexmark.com/printerlicense">www.lexmark.com/printerlicense</a> for details.</li> </ul>

## Warranties

- Limited Warranty**
- See Statement of Limited Warranty:
  - 1-Year Advanced Exchange, Next Business Day

<sup>1</sup>Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

<sup>2</sup>"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

<sup>3</sup>"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

<sup>4</sup>Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.

<sup>5</sup>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)

<sup>†</sup>"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.