

Beacon360 Blaze

Meet the Beacon360 Blaze. The most versatile and durable temporary light on the market. It surpasses military grade drop test requirements by double, see for yourself at www.LindEquipment.net/beacon360blaze. This compact and portable unit provides 14,300 lumens of bright, white light for up to 50' in all directions at full power.

What makes the Blaze unique is its versatility. Use it as task lighting on a tripod to illuminate an entire room. Clamp it to scaffolding on skyscrapers. Place it on a metal beam in an attic. Even daisy-chain it as part of the LED Jobsite System for large area lighting. Whatever your project lighting needs are, the Beacon360 Blaze will meet it.



<u>LE360LED</u> Light head and yoke







<u>LE360LED-MAG</u>
Heavy duty single magnet



<u>LE360LED-CLAMP</u>Adjustable steel clamp



<u>LE360LED-FS</u>
Durable metal floor stand







Beacon360 Blaze

Part of the LED Jobsite

When replacing bulb-based highbays or stringlights on the jobsite, the Beacon360 Blaze will:

- ✓ Reduce your electricity demand and CO₂ emissions by 80%.
- ✓ Last for over 5 years of 24/7 use, transforming your lighting equipment to an asset rather than a disposable.
- ✓ Withstand weather and impact (rugged, durable construction, IP65 weatherproof).
- ✓ Be installed through a simple plug and play system, reducing installation time by up to 95%.
- ✓ Be daisy-chained together on fewer circuits, and their triple-outlet daisy-chain allows for complex patterns of lights to be created.
- ✓ Eliminate hazardous waste sent to landfills from temporary lighting.
- ✓ Require no maintenance.



The versatile Beacon360 Blaze can be mounted to virtually any surface. A tripod, magnet mount, clamp and floor stand, but also a hook for hanging from the ceiling.

The LED Jobsite's plug and play option comes with a **50' daisy-chain cable** which includes a triple-tap connector and a 5-15P plug. Light coverage for up to 50' feet in diameter to 5 foot candles at normal ceiling heights.

	SPECIFICATIONS		
VOLTAGE		90-227V	
	WATTAGE	100W (0.83 amps at 120V)	
k	LIGHT TEMPERATURE 4500K (bright, white light • no blue tint)		
LUMENS14,300 • 7,150 at half powerLIGHT EXPECTANCYRated for over 50,000 hours of 24CONSTRUCTIONCast aluminum housing, polycar		14,300 • 7,150 at ha	lf power
		00 hours of 24/7 use	
		using, polycarbonate lens	
	DIMENSIONS	Height 10.5" • Diameter 6" • Weight 4.5lbs IP65	
	WEATHERPROOF RATING		
	CORD TYPE	LE360LED	15' 18/3 SJOW cord with 5-15P
	CORD TYPE	LE360LED-25P25C	25' with triple outlet & 25' with a 5-15P 14/3 SJTW







