

SPECIFICATIONS

DIMENSIONS (w/o Packaging Material)

Model	3641	3642
Type	Standalone Locker (Host)	Satellite Locker
Width	30-1/8 inches (76.5 cm)	30-1/8 inches (76.5 cm)
Depth – Metal Doors	24-3/4 inches (63 cm)	24-3/4 inches (63 cm)
Depth – Plastic Doors	25-7/8 inches (66 cm)	25-7/8 inches (66 cm)
Height	73-5/16 inches (186.2 cm)	73-5/16 inches (186.2 cm)
Shipping Weight	370 lbs. (Varies with configuration)	370 lbs. (Varies with configuration)

COMPARTMENT SIZES (Standard)

Door Sizes	Opening: Height x Width	Depth
Small	5-1/4 x 11-3/8 inches	21-7/8 inches
Large	10-3/4 x 11-3/8 inches	21-7/8 inches

NOTES:

- Compartment height can be increased by 6" increments using the adjustable kit supplied with each Locker.
- Doors are available in Metal Solid or Metal with Window or Plastic Versions.

ELECTRICAL

Voltage	115 VAC	230 VAC
Cycle	60 Hz	50 Hz
Amperage	2.5 A (Max)	1.25 A (Max)

SAFETY MESSAGES

- Facility over current protection is the main source of over current protection of this appliance.
- If the device is used in a manner not specified by the manufacturer, then the protection provided by the equipment may be impaired.
- Consult local, state, federal codes and regulations before installing the machine.
- Before connecting the machine, the machine electricity supply must be checked for correct polarity, presence of ground and correct voltage.
- If the power supply cord is damaged, it must be replaced by manufacturer, service agent, or similarly qualified individual in order to avoid hazard.
- Care must be taken to turn off all internal power when servicing the machine.
- Access to service area of this machine should be permitted only to individuals having knowledge and practical experience in controller setup and loading.
- For installation of this machine in Canada machine is required to be secured to prevent possible injury.
- Disconnect Power before removing cover at Power Box cutout on the back of the machine.