



Project _____

Item 541HTUC30 Quantity _____

Approval _____ Date _____

MainStreet Equipment HTUC High-Temperature Undercounter Dishwasher - 208V/240V, 1 Phase

Item #541HTUC30

Special Features

- Efficient unit uses only .53 gallons of water per rack
- Cleans up to 22 racks; 792 dishes per hour
- Stainless steel construction is sleek and durable
- Built-in 3kW booster heater allows proper rinse temperatures
- Ideal for commercial kitchens, hotels, and restaurants

Technical Data

Width	23 5/8 Inches
Depth	24 13/16 Inches
Height	32 11/16 Inches
Power Cord Length	6 Feet
Rack Length	20 Inches
Rack Width	20 Inches
Hertz	60 Hz
Phase	1 Phase
Voltage	208/240 Volts
Booster Tank Capacity	1.9 gal.



Certifications



ETL Sanitation



ETL, US & Canada




3/4" Water
Connection



6-20P

Technical Data

Booster Wattage	3 Kilowatts
Dishes Per Hour	792 Dishes
Features	Booster Heater Included Built-In Detergent and Rinse Aid Dispenser Built-In Drain Pump
High or Low Temp	High Temp
Horsepower	3/4 hp
Interior Clearance	15 1/4 Inches
Material	Stainless Steel
Number of Wash Cycles	1 Wash Cycle
Plug Type	NEMA 6-20P
Racks Per Hour	22
Style	Undercounter
Wash Cycle Time	120 Seconds
Wash Pump Wattage	3 Kilowatts
Wash Tank Capacity	5.4 gal.
Water Inlet Size	3/4 Inches
Water Temperature	140 - 180 Degrees F

 **WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.