



Project \_\_\_\_\_

Item 829BMR23R Quantity \_\_\_\_\_

Approval \_\_\_\_\_ Date \_\_\_\_\_

## MainStreet Equipment BMR-23-R 29" Solid Door Reach-In Refrigerator

Item #829BMR23R

### Special Features

- Corrosion-resistant stainless steel exterior with aluminum interior
- Features a self-closing and stay-open locking door
- Includes 3 epoxy-coated shelves with 88 lb. capacity each
- Digital temperature controller with automatic defrost function
- R-290 refrigerant; 115V; 1/4 hp

### Technical Data

Width	29 Inches
Depth	32 3/16 Inches
Height	82 1/2 Inches
Power Cord Length	98 Inches
Interior Width	24 3/8 Inches
Right Door Opening Width	24 5/16 Inches
Interior Depth	27 1/8 Inches
Interior Height	51 9/16 Inches
Amps	3.6 Amps
Hertz	60 Hz



### Certifications



5-15P



ETL Sanitation




ETL, US

Intertek

## Technical Data

<b>Phase</b>	1 Phase
<b>Voltage</b>	115 Volts
<b>Wattage</b>	348 Watts
<b>Capacity</b>	23.1 cu. ft.
<b>Capacity (per Shelf)</b>	88 lb.
<b>Compressor Location</b>	Bottom Mounted
<b>Construction</b>	Stainless Steel and Aluminum
<b>Door Type</b>	Solid
<b>Hinge Location</b>	Right
<b>Horsepower</b>	1/4 hp
<b>Installation Type</b>	Freestanding
<b>Material</b>	Aluminum / Stainless Steel
<b>Number of Doors</b>	1 Doors
<b>Number of Shelves</b>	3 Shelves
<b>Plug Type</b>	NEMA 5-15P
<b>Power Type</b>	Electric
<b>Refrigerant Capacity</b>	2.6 oz.
<b>Refrigerant Type</b>	R-290
<b>Sections</b>	1 Section
<b>Starting Amps</b>	10.8 Amps
<b>Starting Wattage</b>	1044 Watts
<b>Temperature Range</b>	32 - 40 Degrees F
<b>Type</b>	Refrigerators

 **WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).