



Metro® Stem Casters

We put space to work.®

Stainless Steel, Cart-Washable Casters

- Designed with sealed stainless steel bearings to withstand high-pressure washings and zerk fittings for easy routine maintenance. For medium duty applications. Bumpers included. NSF listed.
- Non marking tread
- Brake style: Pedal brake.

Wheel Diameter (in.) (mm)	Face (in.) (mm)	Load Rating (lbs.) (kg.)	Type	Wheel Tread	Temperature range (Continuous usage)		Apprx. Pkd. Wt.		Cat. No.
					(Fahrenheit)	(Celsius)	(lbs.)	(kg.)	
5 127	1-1/4 32	250 113	Stem/Swivel	High Modulus Donut	-20° - 180°	-29° - 82°	2-1/2	1.1	5MDGSA
5 127	1-1/4 32	250 113	Stem/Brake	High Modulus Donut	-20° - 180°	-29° - 82°	2-5/8	1.2	5MDBGSA
5 127	1-1/4 32	250 113	Stem/Rigid	High Modulus Donut	-20° - 180°	-29° - 82°	2-3/8	1.1	5MDRGSA
5 152	1-1/2 38	300 135	Stem/Swivel	Polyurethane, Flat	-20° - 180°	-29° - 82°	2-1/8	0.9	5MPGSA
5 152	1-1/2 38	300 135	Stem/Brake	Polyurethane, Flat	-20° - 180°	-29° - 82°	2-1/4	1	5MPBGSA
5 152	1-1/2 38	300 135	Stem/Rigid	Polyurethane, Flat	-20° - 180°	-29° - 82°	2	0.9	5MPRGSA

Note: Rigid connecting channel (stainless steel): Cat. No. 14RS, 18RS, 21RS, 24RS, 30RS, or 36RS.



5MDGSA



5MDBGSA



5MDRGSA



5MPGSA



5MPBGSA



5MPRGSA



**Bumper
included with
these models.**

Rigid stem casters are often ordered two per unit for improved tracking and handling. Rigid caster channels are provided with each two rigid stem casters at no charge.

Low Profile 3" Threaded Stem Casters

- Threaded stem installs into the base of a standard stationary post.
- Resilient rubber tread. Bumpers not included.

Wheel Diameter (in.) (mm)	Face (in.) (mm)	Load Rating (lbs.) (kg.)	Type	Wheel Tread	Temperature range (Continuous usage)		Apprx. Pkd. Wt.		Cat. No.
					(Fahrenheit)	(Celsius)	(lbs.)	(kg.)	
3 76	15/16 24	100 45	Stem/Swivel	Resilient Rubber	-20° - 130°	-29° - 71°	1.0	0.45	3TM
3 76	15/16 24	100 45	Stem/Brake	Resilient Rubber	-20° - 130°	-29° - 71°	1.1	0.50	3TMB



3TM



3TMB