

Specification of Namco Crawl Space Dehumidifer

Photos			
Model Number	RW-95	RW-150	RW-190
Air inlet and outlet	Front in, Side out	straight in straight out	straight in straight out
Machine size	20.7" X 13.0" X 13.0" (525*330*330mm)	21.7" X 13.0" X 13.0" (550*330*330mm)	12.6" X 15.0" X 17.7" (600*380*450mm)
Package Size	25.8" X 15.4" X 15.9" (655*390*405mm)	24.0" X 16.1" X 15.9" (610*410*405mm)	26.0" X 18.1" X 20.7" (660*460*525mm)
Dehumidification capacity (30°C/86F, 80%)	95 pints (45L/day)	150 pints (72L/day)	190 pints (90L/day)
Room Size For	Up to 1,300 Sq.ft	Up to 2,600 Sq.ft	Up to 3,300 Sq.ft
Machine weight	47.4lbs (21.5kg)	51.8lbs (23.5kg)	68.4lbs (31kg)
Air volume	165CFM(280m³/h)	235CFM(400m³/h)	324CFM(550m³/h)
Power supply	110V/50-60Hz	110V/50-60Hz	110V/50-60Hz
Rated power	380W	520W	820W
Refrigerant	R410a(260g)	R410a(300g)	R410a(520g)
Noise	32dB	35dB	45dB
Functioning Temperaturn Range	33.8F to 104F	33.8F to 104F	33.8F to 104F
Functioning Humifity Range	36 to 90%	36 to 90%	36 to 90%
Drainage method	Water pump	Water pump	Water pump
Water pump lift	10ft (3m)	10ft (3m)	10ft (3m)
Water pipe length(tentative)	26.3ft (8m)	26.3ft (8m)	26.3ft (8m)
Pump type	tank pump	tank pump	tank pump
Power length (tentative)	10ft (3m)	10ft (3m)	10ft (3m)
Control method(optional)	Remote control/86 controller	Remote control/86 controller	Remote control/86 controller
Hook accessories	optinal	optinal	optinal
Fan type	Forward inclined centrifugal fan	Backward inclined centrifugal fan	Backward inclined centrifugal fan
Filter level	G4/MERV-8 (thickness 10mm)	F6/MERV-10 (thickness 20mm)	F6/MERV-10 (thickness 20mm)
Tuyere	Φ150	/	/
Remote control picture (Include)			
86 control screen pictures (Optional)			