### **Tables**



### SLT2448/SLT2454/SLT2460/SLT2472/SLT3060/SLT3072/SLTL-36

SCIENCE LAB TABLE
-30"H 8.36"H tables available in 24" 8.30" width
-24"W table available in 48", 54", 60" and 72" lengths
-30"W table available in both 60" 8.72" lengths

Solid ash legs and apron

- วดเต asn legs and apron

Optional book compartments measuring 14 1/4"L x 12 3/4"D x 4"H

Legs attach with metal on metal double bolt through assembly on 13-gauge steel corner braces

Rubber liquid protecting boots

Adjustable glides for accurate leveling

Top Finish Options:
- Black, Chem-Res high-pressure laminate top on a 1 1/8" thick core. Resistant to 13 chemicals:

NO.	CHEMICAL COMPOUND	CHEMICAL NAME	STAIN GRADE	TEST METHODS
1	NaOH (40%)	Sodium Hydroxide	0	NEMA LD3-2005
2	H <sub>2</sub> O <sub>2</sub> (3%)	Hydrogen Peroxide	0	NEMA LD3
3	HCI (37%)	Hydrochloric Acid	0	NEMA LD3
4	CH₃COOH (99%)	Acetic Acid	0	NEMA LD3
5	H <sub>2</sub> SO4 (98%)	Vitriol	0	NEMA LD3
6	HNO <sub>3</sub> (65%)	Nitric Acid	0	NEMA LD3
7	H₃PO4 (85%)	Phosphoric Acid	0	NEMA LD3
8	HF (48%)	Hydrofluoric Acid	0	NEMA LD3
9	Formaldehyde (37%)	Formalllin	0	NEMA LD3
10	NH4OH (25%)	Ammonia	0	NEMA LD3
11	Phenol	Phenol	0	NEMA LD3 - 2000
12	Na <sub>2</sub> S	Saturated Sodium Sulfide	0	NEMA LD3 - 2000
13	CCI4	Carbon Tetrachloride	0	NEMA LD3 - 2000

- Black, solid 3/4 phenolic resin composite thermo-fused under heat and pressure to form a solid black chemical resistant panel.
- Highly impervious to most chemicals, acids, corrosions, stains and moisture.
- Meant for tough use, comparable to Epoxy Resin tops, Emission free, UV Resistant
- Solid phenolic throughout allowing for easy care and maintenance

BT3060/BT3072/BT3096
LIGHTWEIGHT BLOW MOLDED FOLDING TABLES

. Available in 3 rectangular sizes – 60", 72", 96"

1 3/4" thick top for the BT3060 & BT3072

2" thick top for the BT3096
. Lightly spotted grey top w/ grey textured powder coated wishbone shaped legs.
17-gauge strength frame; 18-gauge legs
1,000lb. weight capacity on BT3060, BT3072
. 800lb. weight capacity on BT3096
. Stack up to 12 high on DY3072 and DY3096
. Can withstand heat up to 212 degrees Fahrenheit
. Gravity slide lock or snap lock, for extra stability
. Lightly textured surface to resist scratching yet smooth enough to write on

#### BT48R/BT60R/BT71R

BT48R/BT60R/BT71R

LIGHTWEIGHT BLOW MOLDED ROUND FOLDING TABLES

Available in 3 round sizes - 48", 60", 71"

-2" thick top

Lightly spotted grey top w/ grey textured powder coated straight legs

BT608: 17-gauge strength frame; 18-gauge legs

BT48R 8 BT71R: 19-gauge strength frame and legs

1,000lb. weight capacity on BT60R

700lb. weight capacity on BT40R 8 BT71R

Holds up to 10 tables in DY60R and DY71R

Can withstand heat up to 212 degrees Fahrenheit

Gravity slide lock or snap lock, for extra stability

Lightly textured surface to resist scratching yet smooth enough to write on

#### BTA-3072

ALL AMERICAN COLORS BLOW MOLDED FOLDING TABLES
-Available in 72"L rectangular size
-13/4" thick top

13/4" thick top
Lightly spotted grey top w/ grey textured powder coated Pedestal style legs.
BTA-3072 comes in primary colors Red or Blue & is height adjustable from 22"-32"H.
17-gauge strength frame
1,000lb. weight capacity
Stack up to 12 high on DY3072 and DY3096
Can withstand heat up to 212 degrees Fahrenheit
Gravity slide lock or snap lock, for extra stability
Lightly textured surface to resist scratching yet smooth enough to write on

BT1860/BT1872/BT1896
LIGHTWEIGHT FOLDING SEMINAR TABLES
Available in 3 sizes; 60°L, 72°L & 96°L by 18°W
2-inch thick top
Lightweight for easy set-up and transport
700lb. weight capacity
Lightly spotted gray top w/ gray textured powder coated legs
BT1860 & BT1872: 18-gauge strength frame
BT1896: 17-gauge strength frame
BT1896: 17-gauge strength frame
16-gauge cantilevered comfort legs set 11" from back of table; no more banged up knees!
Stack up to 12 high on DY3072 and DY3096
Can withstand heat up to 212 degrees Fahrenheit
Lightly textured surface to resist scratching yet smooth enough to write on

BPFT
PLASTIC FLIP·N·STORE TABLES
Tops are made of lightweight HDPE blow molded plastic.
Tops are furnished with two grommet holes for wire management.
Equipped with dual levers, allowing for easy tabletop folding
Tables nest together for space-saving storage.
Frame and legs are made of grey hammer-tone powdercoated steel and includes a perforated steel modesty panel for an attractive design.
Modesty panel features a built-in cable channel to conceal wires.
Tables are equipped with four 2" casters (two locking) making them easy to roll.
Tables tested to support up to 700 lbs. and are guaranteed for ten years.
MAS certified Green®
Tables are lightweight weighing only 48 lbs. and are easy to assemble.
Opened dimensions are 60"L x 24"W x 29½"H
Folded dimensions are 43½"H x 60"L x 24½"W
Tabletop thickness: 1½"
Gauge of steel: 16 gauge
Carton dimensions are 62"L x 29" W x 9" D. Carton weight 58 lbs.
Ships with UPS oversize or by truck at class 85.

# Stages & Risers



#### PERFORMANCE STAGES AND SEATED RISERS

INCLUDES 36"W AND 48"W STAGES STAGE PIECES, STAGE PIES, & STAGE SETS Constructed with 3/4" solid plywood core

Constructed with carpet in choice of 4 colors or 1/8" thick tempered hardboard

16-gauge, 1-13/16" high formed sted channel frame reinforced with 16-gauge steel angle welded to the inside of the channel

14-gauge steel tubing capped at the point of floor contact with high impact plastic glides

- 14-gauge steel tubing capped at the point of floor contact with high impact plastic glides
- Lega open and close using only one hand
- Stages and risers equipped with drop-in couplings that allow units of same or different heights to be joined together
- All ganging devices are permanently secured to each unit
- Exceeds 200 lbs. per square foot load bearing capacity
- Available in 36" and 48" widths
- Comes in 4 heights; 8", 16", 24" and 32"
- Skirting available for all stages in 2 styles; shirred pleat and box pleat
- Optional Stage Pies for semi-circle arrangements
- 3 step heights available to connect to 16"H Stages and above
- Optional Guardrails recommended for safety. Guardrails are 14-gauge
- 10-year warranty

### **CHORAL RISERS** / RS AND RT SERIES

CONSTRUCTED WITH SOLID PLAN AND KT SERIES

Constructed with 3/4" solid plywood core

Available with carpet in choice of 4 colors or 1/8" thick tempered hardboard

16-gauge, 1-13/16" high formed steel channel frame reinforced with 16-gauge steel angle welded to the inside of the channel

14-gauge steel tubing capped at the point of floor contact with high impact plastic glides

Legs open and close using only one hand

Equipped with drop-in couplings that allow units of same or different heights to be joined together

All propriets divisors are perspectable research to each unit.

All ganging devices are permanently secured to each unit Exceeds 200 lbs. per square foot load bearing capacity Comes in 4 heights; 8", 16", 24" and 32" Straight and Tapered units for continuous and semi-circle configurations

Optional Guardrails recommended for safety 10-year warranty

TRANS-PORT RISER

Available in three 18" wide levels; 8", 16" and 24" high that are permanently joined with hinge mechanisms to enable the unit to open and close in a unified fashion
Each unit is equipped with wheek for easy transportation when folded and to allow for easy positioning after set up
Riser levels supported by a 3" deep, double walled, extruded anodized aluminum frame that overlaps the top of each level to protect the carpet edge
Riser platforms constructed of 3/4" plywood, surfaced with polyolefin carpet
Optional guardrails constructed of black epoxy powder-coated tubular steel and equipped with clampon attachnests for easy installation

o patient goal and scored to the key ploys powder-coated about steel and equipped with clamp-on attachments for easy installation Straight or Tapered units available for various configurations Now avail: 4th Level Add-On: TPA: 18-1/8"W x 72 1/2"L x 32 1/2"H TPRA: 18"W x 79"L x 32 1/2"H Standing Capacity: TPT2: 15-18 adults (with 4th level #TPA: 20-23) TPR72: 11-14 adults (with 4th level #TPRA 16-19) 10-year warranty

# **Stage Accessory Parts**

## STP16/STP24/STP32 / STEPS FOR STAGES

DIMENSIONS: STP16: 36"W X 14"D X 48"H, 42 LBS. STP24: 36"W X 28"D X 56"H, 72 LBS. STP32: 36"W X 42"D X 63"H, 110 LBS.

Made of high grade plywood edged with vinyl t-molding
 Steps coated with Polypropylene textured surface
 Frame is built with 14 gauge steel tubing
 Frame is built with 14 gauge steel tubing

### GRR24S/GRR32S/GRR24T/GRR32T / BACK GUARDRAILS FOR RISERS

DIMENSIONS: GRR24S 94"L X 66"H, 51 LBS. GRR32S 94"L X 74"H, 55 LBS. GRR24T 70"L X 66"H, 40 LBS. GRR32T 76"L X 74"H, 43 LBS.

For use with Straight & Tapered Risers Top and bottom horizontal tubes are 1 ½" 0.D.

Black powdercoated steel Middle horizontal tubes are 1" 0.D.

All tubes are 14 gauge steel Ends of tubes are outfitted with high impact

Black powdercoated steel
All tubes are 14 gauge steel
Vertical tubes are 1 ½" O.D. plastic flower end-caps.

GRTPR3 / GRTPR4 / BACK GUARDRAILS FOR TRANS-PORT RISER

DIMENSIONS: GRTPR3 70 1/2"L X 66 1/4"H, 69 LBS. GRTPR4 70 1/2"L X 74 1/4"H, 75 LBS.

For use with Straight & Tapered Trans-port Risers Black powdercoated steel All tubes are 14 gauge steel Vertical tubes are 1  $^{\prime\prime}$  ° 0.D. - Ends of tubes are outfitted with high impact plastic flower end-caps.

Black powdercoated steel
All tubes are 14 gauge steel
Vertical tubes are 1 1/4" O.D.

# SGRTP3 / SGRTP4 / SIDE GUARD RAILS FOR TRANS-PORT RISERS

DIMENSIONS: GSGRTP3 59 1/4"L X 63 1/2"H, 10 LBS. SGRTP4 79 1/4"L X 71 5/8"H, 11 LBS.

For use with Straight & Tapered Trans-port Risers · Vertical and horizontal tubes are 1 1/4" O.D. · Ends of tubes are outfitted with high impact Black powdercoated steel All tubes are 14 gauge steel plastic flower end-caps.

## GRS30/GRS36/GRS48 / GUARDRAILS FOR STAGES

DIMENSIONS: GRS30 30"L X 30"H, 12 LBS. GRS36 36"L X 30"H, 13 LBS. GRS48 48"L X 30"H, 15 LBS.

For use with stages
Black powdercoated steel
All tubes are 14 gauge steel
Vertical tubes are 1 1/4" O.D.

- Top horizontal tube is 1 ½" O.D. - Middle and bottom horizontal tubes are 1" O.D. - Ends of tubes are outfitted with high impact plastic flower end-caps.

## SGR2L/SGR3L/SGR4L /SIDE GUARD RAILS FOR STANDARD RISERS

DIMENSIONS: SGR2L 37 7/8"L X 30 7/8"H, 8 3/4 LBS. SGR3L 57 1/3"L X 28 5/8"H, 11 LBS. SGR4L 77 1/4"L X 30 7/8"H, 12 LBS.

· Vertical and horizontal tubes are 1 1/4" O.D. For use with standard risers Black powdercoated steel
 All tubes are 14 gauge steel · Ends of tubes are outfitted with high impact plastic flower end-caps.

# CG28/CG32/CG37/CG44/CG54/CG72/CG81/CG96 / CHAIR GUARDS

DIMENSIONS: CG28 28"L, 3 LBS. CG32 32"L, 3 LBS. CG37 37"L, 3½ LBS. CG44 44"L, 3½ LBS. CG45 54"L, 4 LBS. CG72 72"L, 4½ LBS. CG81 81"L, 5 LBS. CG96 96"L, 5½ LBS

For use with stages and stage pies
 Tube is made of 1" O.D.
 Tube is 14 gauge steel.

Ends of Chair Guards are outfitted with high impact plastic flower end-caps.
Chair Guards are powdercoated in black.

### SDL / STAGE DOLLY

DIMENSIONS: 44"1 X 30"W X 60" H- WEIGHS 65 LBS

Capacity: Six stages
Can be used for both 36" 48" stages
Built with 14 gauge tubular steel Rolls on four 5" casters