



## Noble Warewashing HT-UC24 Select High-Temperature Undercounter Dishwasher with Booster Heater-208/240V, 1 Phase

#495HTUC24

Item #: 495HTUC24 Qty: \_\_\_\_\_

Project: \_\_\_\_\_

Approval: \_\_\_\_\_ Date: \_\_\_\_\_



### Features

- Simple top-mounted digital display and control panel
- Washes up to 24 racks per hour using only 0.84 gallons of water per rack
- 14 7/16" door opening accommodates tall glassware
- Double-wall, labyrinth-style door prevents water, steam, and heat from escaping
- Recirculating design uses less water and energy than fill-and-dump models

### Certifications



Hardwired



3/4" Water Connection



NSF Certified



Energy Star Qualified



UL Certified

### Technical Data

Width	22 11/16 Inches
Depth	24 Inches
Height	32 5/16 Inches
Amps	24.2 - 27.5 Amps
Hertz	60 Hz
Phase	1 Phase
Voltage	208/240 Volts
High or Low Temp	High Temp
Horsepower	1 hp
Material	Stainless Steel

## Technical Data

Features	Auto Fill Booster Heater Included Built-In Drain Pump Energy Star Qualified NSF Certified
Number of Wash Cycles	2 Wash Cycles
Plug Type	Hardwire
Racks (per Hour)	24
Style	Rack
Type	Undercounter Dishwashers
Wash Cycle Time	100 - 360 Seconds
Wash Tank Capacity	5.3 gal.
Water Inlet Size	3/4 Inches
Water Temperature	110 - 140 Degrees F
Water Usage	0.84 Gallons Per Rack

## Notes & Details

Get spotless dishes every time with this Noble Warewashing high-temperature dishwasher. This dishwasher uses hot water to quickly sanitize dishes and wash away residue such as grease, baked-on food, and lipstick. It washes up to 24 racks per hour using only 0.84 gallons of water per rack. Each cycle begins with a soft start and fills automatically. It also allows cycles to be extended by 6 minutes. This unit's integrated electric booster heater has 2 cycle options and increases the temperature by 70 degrees Fahrenheit. Its recirculating wash system uses less water and energy than traditional fill-and-dump models.

This dishwasher emits only 63 decibels for quiet, non-disruptive operation. It is easy to use with a top-mounted digital display and simple control panel. It includes integrated wash and rinse arms for comprehensive coverage. This unit also features an automatic pumped drain to remove wash and rinse water at the end of each cycle. Its delime notification and cycle simplifies maintenance.

The dishwasher enables a slow ramp up of water pressure. It has a 14 7/16" door opening for easy loading and unloading and to accommodate tall glassware. Its double-wall, labyrinth-style door prevents water, steam, and heat from escaping. This dishwasher requires a 208/240V, 1 phase electrical connection for operation.

**⚠ WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).