



## Noble Warewashing UH30-FND High Temperature Undercounter Dishwasher with 10" Adjustable Stand - 208/230V

#495UH30KIT8

Item #: 495UH30KIT8 Qty: \_\_\_\_\_

Project: \_\_\_\_\_

Approval: \_\_\_\_\_ Date: \_\_\_\_\_



### Features

- Cleans up to 24 racks per hour using 1.1 gallons of water per rack
- Sani-Sure feature and built-in booster heater for proper rinse water temperatures
- Auto-fill, 2-minute automatic cycle, and deliming cycle
- Sleek stainless steel construction with an air insulated design to retain heat
- Includes stand to reduce bending and back strain

### Certifications



ETL Sanitation

ETL, US & Canada



Hardwired



Energy Star Qualified



3/4" Water Connection

### Technical Data

|                 |                         |
|-----------------|-------------------------|
| Width           | 24 1/4 Inches           |
| Depth           | 25 Inches               |
| Height          | 33 5/16 Inches          |
| Interior Width  | 20 Inches               |
| Interior Depth  | 20 Inches               |
| Interior Height | 14 1/2 Inches           |
| Stand Height    | 9 7/16 - 10 7/16 Inches |
| Hertz           | 60 Hz                   |
| Phase           | 1 Phase                 |
| Voltage         | 208 - 230 Volts         |

## Technical Data

|                       |  |
|-----------------------|--|
| Features              | Adjustable<br>Booster Heater Included<br>Chemical Pumps<br>Energy Star Qualified<br>Stand Included |
| Glasses (per Hour)    | 864  |
| High or Low Temp      | High Temp  |
| Horsepower            | 1 hp   |
| Interior Clearance    | 14 1/2 Inches  |
| Number of Wash Cycles | 3 Wash Cycles  |
| Plug Type             | Hardwire   |
| Racks (per Hour)      | 24   |
| Type                  | Undercounter Dishwashers   |
| Wash Cycle Time       | 82 Seconds   |
| Water Inlet Size      | 3/4 Inches   |
| Water Temperature     | 150 - 180 Degrees F  |
| Water Usage           | 1.1 Gallons Per Rack   |

## Notes & Details

Quickly, easily, and efficiently clean full racks of used dishes with the Noble Warewashing high temperature undercounter dish machine and its compatible 10" adjustable stand. The power of this dishwasher combines with the convenience of a stand that elevates the machine and reduces strain to create an ideal asset for your busy foodservice establishment. The durable stainless steel stand has a height of 9 7/16" with adjustable feet that can raise it to 10 7/16". Keeping your dishes and glasses clean is essential to the life of your business, and thanks to this durable unit, you can successfully clean up to 24 racks per hour with 1.1 gallons of water per rack! This ensures that you'll always be able to keep up with peak hours of service at your establishment.

For maximum cleaning power, the unit features several bonus cycles. The fresh water rinse works to prevent possible wash water contamination, keeping dishes thoroughly clean and safe to use. Plus, the convenient deliming cycle makes quick work of removing hard water deposits, so your dishes will be left sparkling clean every time. Thanks to its compact, undercounter design, the unit is perfect for kitchens with limited space available and a need for efficient warewashing. Made with rugged stainless steel, this machine is built to withstand heavy-duty use in a commercial kitchen.

To start the machine simply press the start button, wait for the LED light to turn green, close the door, and press start again. The unit fills, thanks to the automatic fill feature, and the cycle starts. During the cycle, you can easily track its progress with the universal timer. To accommodate a variety of drain installations, the drain automatically pumps while the unit runs with the powerful, stainless steel, 1 hp wash pump.

This high temperature warewashing machine comes with a booster heater that helps the unit achieve appropriate rinse temperatures. Because it's already built-in, the booster heater eliminates the need to take extra electrical requirements into account. An exclusive Sani-Sure feature also aids in assuring proper temperatures throughout operation. This unit requires a 208/230V electrical connection for operation.

**⚠ WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).