

Non-Refrigerated Service Countertop Case

- ☐ NR3627DSV
- ☐ NR4827DSV

Lengths include end panels
35-3/4"L x 32-5/8"D x 27-7/8"H
47-3/4"L x 32-5/8"D x 27-7/8"H



STANDARD FEATURES

- NOTE: Glass warranty only applicable to first point of delivery
- NOTE: Cannot be joined case to case
- (2) Levels of clear glass shelving removable and adjustable on 1" centers
- LED top & shelf lights
- One year parts & labor warranty
- Vertical, fixed front & side UV bonded frameless glass

Features	Standard	Options
EXTERIOR COLOR	☐ Black	☐ Painted (non-stock colors, specify RAL#) ☐ Painted (stock colors, specify RAL#) ☐ Stainless steel
INTERIOR COLOR	☐ Black	☐ NOTE: Interior color must be FDA & NSF approved ☐ Painted (stock colors, specify RAL#) ☐ Stainless steel
UPPER REAR	☐ Clear glass rear sliding doors	☐ Reflective glass rear sliding doors
LIGHTS	☐ LED 3500K w/ frosted lens	☐ LED 3000K w/ frosted lens ☐ LED 4000K w/ frosted lens
ELECTRICAL CONNECT	☐ 6' Straight blade power cord	☐ 6' Locking blade power cord ☐ Electrical leads (non-refrigerated)
MISCELLANEOUS		☐ Rear door lock ☐ Second year parts & labor warranty

Reveal®



Product Specifications

Intended Environment: Type I - Designed to operate in ambient conditions of 75°F with 55% relative humidity unless noted otherwise in system information below.		
Zone	Intended Product To Be Displayed	Warmest Avg Prod Temp ° F
1	Unpackaged non-refrigerated products	Ambient

REAR VIEW

PLAN VIEW

SIDE VIEW



NOTE: ALL DIMENSIONS APPROXIMATE

- ELECTRICAL JUNCTION BOX (SUPPLIED WITH 6" LEADS OR POWER CORD).
- LOCATION OF DRAIN TUBE FOR REMOTE REF. ONLY (SUPPLIED WITH 3/4" OR 1 1/2" PVC TUBE).

- REFRIGERATION LINE CONNECTION.
- REMOTE FLOOR SINK & UTILITIES ACCESS AREA.

- SELF-CONTAINED CASE SERVICE ACCESS AREA.
- DRY CASE SERVICE ACCESS AREA.

Model Technical Specifications																
Model	L"	L1"	L2"	System Circuit Volts			Phs	Freq	Amps ***	Watts	Wires	NEMA Plug	SST	Conv. Rack BTUH	Para. Rack BTUH	Est Wt
NR3627DSV	N/A	35.75	.00	Ambient/Lights	Circuit #1	110-120	1	60	0.70	11	2+G	5-15P or L5-15P	N/A	N/A	N/A	400
NR4827DSV	N/A	47.75	.00	Ambient/Lights	Circuit #1	110-120	1	60	0.70	17	2+G	5-15P or L5-15P	N/A	N/A	N/A	500

*** Does not include electric defrost on freezer models.

Regulatory Approvals:

All Models	ETL Listed to UL 65 ETL Sanitation to NSF 2
------------	--



Important Notes:

- 1) ELECTRICAL NOTE: If GFCI is required, a GFCI breaker MUST be used in lieu of a GFCI receptacle.
- 2) Glass warranty only applicable to first point of delivery.
- 3) Cannot be joined case to case.

WARNING: This product can expose you to chemicals, including Urethane (Ethyl Carbamate), which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.