

ITEM NO:	
PROJECT:	
DATE:	

## Non-Refrigerated Self-Service Case

□ NR3640DSSV □ NR4840DSSV

Lengths include end panels 35-3/4"L x 33"D x 39-5/8"H 47-3/4"L x 33"D x 39-5/8"H

## **STANDARD FEATURES**

- NOTE: Glass warranty only applicable to first point of delivery
- (1) Level of clear glass shelving removable and adjustable on 1" centers
- LED top & shelf lights
- One piece formed ABS plastic tub
- Second year parts & labor warranty

Features	Standard	Options
EXTERIOR COLOR	□ Black	□ Painted (non-stock colors, specify RAL#)
		□ Painted (stock colors, specify RAL#)
		□ Stainless steel
NTERIOR COLOR	□ Black	□ NOTE: Interior color must be FDA & NSF approved
		□ Painted (stock colors, specify RAL#)
		□ Stainless steel
PANEL EXTERIOR	□ Laminated (non-premium) Confirm	□ Laminated (premium) Confirm pattern/grain direction
	pattern/grain direction	□ Stainless steel
BASE SUPPORT	□ Adjustable, locking casters	□ 6"H stainless steel legs
END PANEL LEFT	□ Full end panel	□ No end panel
END PANEL RIGHT	□ Full end panel	□ No end panel
LOWER FRONT PANEL	□ Black	□ Painted (stock colors, specify RAL#)
		□ Stainless steel
LOWER REAR PANEL	□ Black	□ Painted (stock colors, specify RAL#)
		□ Stainless steel
JPPER REAR	□ Solid back panel	□ Clear glass rear sliding doors
		□ Reflective glass rear sliding doors
LIGHTS	□ LED 3500K w/ frosted lens	□ LED 3000K w/ frosted lens
		□ LED 4000K w/ frosted lens
ELECTRICAL CONNECT	□ 6' Straight blade power cord	□ 6' Locking blade power cord
		□ Electrical leads (non-refrigerated)
MISCELLANEOUS		□¹ 14.5" Base height extension
		□ Rear door lock
		□ Second year parts & labor warranty
ACCESSORIES		□ Clear acrylic security cover, removable, locking
		□ Price tag molding (matches interior color) (CDR7658

Option Notes: 1 - Cannot be combined w/ 6"H legs






Intended Environment: Type I - Designed to operate in ambient conditions of 75°F with 55% relative humidity unless noted otherwise in system information below.


 Zone
 Intended Product To Be Displayed
 Warmest Avg Prod Temp ° F


 1
 Packaged non-refrigerated products
 Ambient

**PLAN VIEW** 

SIDE VIEW







## NOTE: ALL DIMENSIONS APPROXIMATE

 ■ ELECTRICAL JUNCTION BOX (SUPPLIED WITH 6" LEADS OR POWER CORD).
 ■ LOCATION OF DRAIN TUBE FOR REMOTE REF. ONLY (SUPPLIED WITH 34" OR 1½" PVC TUBE).

REFRIGERATION LINE CONNECTION.

REMOTE FLOOR SINK & UTILITIES
ACCESS AREA.


SELF-CONTAINED CASE SERVICE ACCESS AREA.

DRY CASE SERVICE ACCESS AREA.

Model Technical Specifications																
Model	L"	L1"	L2"	System	Circuit Volts		Phs	Freq	Amps	Watts	Wires	NEMA Plug	SST	Rack	Para. Rack BTUH	Est Wt
NR3640DSSV	N/A	35.75	.00	Ambient/Lights	Circuit #1	110-120	1	60	0.70	8	2+G	5-15P or L5-15P	N/A	N/A	N/A	550
NR4840DSSV	N/A	47.75	.00	Ambient/Lights	Circuit #1	110-120	1	60	0.70	11	2+G	5-15P or L5-15P	N/A	N/A	N/A	750

\*\*\* Does not include electric defrost on freezer models.

Regulatory Approvals:					
All Models	ETL Listed to UL 65				
	ETL Sanitation to NSE 2				



**Important Notes:** 

- 1) ELECTRICAL NOTE: If GFCI is required, a GFCI breaker MUST be used in lieu of a GFCI receptacle
- 2) Glass warranty only applicable to first point of delivery.

**WARNING:** This product can expose you to chemicals, including Urethane (Ethyl Carbamate), which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.