

XO-1 | XO-1M | RM-5T | RA-5T

NU-VU® Countertop Ovens



The XO-1 and XO-1M are smaller ovens with the ability to hold either three or four half-size sheet pans. Don't let their size fool you; these little ovens are true work horses. Constructed of stainless steel, and full view tempered glass doors, these ovens are designed to be compact yet heavy-duty.

The RM-5T and RA-5T are constructed of stainless steel, and incorporate NU-VU's V-AIR® technology to ensure a perfect bake. The slam cam handle and cool to touch dual pane door provide safe and easy usage. A pass-thru option is available, and allows back of the house loading, with front of the house unloading. Just 30" wide, and the ability to be stacked, it is the perfect convection oven to add where space may be limited.



XO-1



XO-1M



RM-5T



RA-5T (Shown with Pass-thru Option)

Features

XO-1 & XO-1M OVENS

- Temperature up to 550 °F (288 °C)
- Stainless steel construction
- Two speed fan
- Full view tempered glass door
- Indicator light for thermostat
- Left hinged
- 4" adjustable legs (102 mm)
- NSF listed
- 2 year parts, 1 year labor warranty

Options

- Internal steam
- Solid door
- Stand on swivel casters with panslides
- Stand with or without panslides
- Catering conversion (XO-1 only)

RM-5T & RA-5T OVENS

- V-Air® technology
- Manual control (RM)
- Digital control with up to 99 recipes (RA)
- Temperature up to 425 °F (218 °C)
- Stainless steel construction
- Stainless steel legs (6")
- Cool to touch, dual pane, full view tempered glass door
- Field reversible door
- Left or right hinged (please specify upon ordering)
- Slam Cam handle
- ETL and ETL Sanitation Listed
- 2 year parts, 1 year labor warranty

Options

- Pass thru
- Two speed fan
- Stand on swivel casters with or without panslides
- Stand with or without panslides
- Stacking kit
- Internal Steam
- Cook'n hold
- Water softener

Voltage



120 Volt, 16 Amp
(NEMA 5-20P)
(XO-1 only)

Specifications

Model	Crated Weight	Overall Dimensions			Interior Dimensions			Pan Capacity	Shelf spacing	Water Inlet	Electrical System * Ground wire not included.						
		W	D	H	W	D	H				Volts	Phases	Amps	kW	Wires*	Hz	NEMA
XO-1	140 (64)	27 1/8" (689)	27 3/4" (705)	20" (508)	15 3/4" (400)	21 1/2" (546)	11 3/4" (298)	3 (half pans) 4 (half pans)	3 3/4" (96) 2" (51)	1/4"	120	1	16.5	1.7	2	60	5-20P
XO-1M	180 (82)	27 1/8" (689)	27 3/4" (705)	25 1/8" (638)	15 3/4" (400)	21 1/2" (546)	16 3/4" (424)	4 (half pans) 5 (half pans)	3" (76) 3 5/8" (92)	1/4"	208 240	1 1	21/20 19/17	4 4	2/3 2/3	60 60	— —
RM-5T	400 (181)	30" (762)	37 7/8" (962)	41 3/4" (1060)	18 3/4" (476)	29 3/4" (755)	22" (559)	5 (full pans)	4" (102)	1/4"	208 240	1/3 1/3	37/30 32/26	7 7	2/3 2/3	60 60	— —
RA-5T	400 (181)	30" (762)	37 7/8" (962)	41 3/4" (1060)	18 3/4" (476)	29 3/4" (755)	22" (559)	5 (full pans)	4" (102)	1/4"	208 240	1/3 1/3	37/30 32/26	7 7	2/3 2/3	60 60	— —