



ZINSSER® ODORLESS PRIMER-SEALER STAIN BLOCKER

DESCRIPTION AND USES

Zinsser® Odorless aerosol is an easy to use, all-purpose, low odor primer-sealer and stain blocker. It is designed for interior applications where oil-base performance is required but odor is a concern. It is suitable for sealing nicotine, fire, smoke and water stains on surfaces such as wood molding, trim and spackled areas. It adheres to paneling, kitchen cabinets, glossy paints and hard-to-paint objects, such as wicker, louvers, picture frames, and arts and crafts. It is compatible with all latex and oil-based architectural paints.

PERFORMANCE CHARACTERISTICS

- Blocks water, smoke and tannin stains
- Bright white finish, non-yellowing formula
- No lingering odor
- Adheres to all surfaces
- Recoat in 2 hours

PRODUCT

SKU	DESCRIPTION
3959	13 Ounce Spray

PRODUCT APPLICATION

SURFACE PREPARATION

Surfaces should be clean, dry, sound and free of dust, dirt, grime, grease, oil, wax, mildew, wallpaper, adhesive or any contamination that may interfere with adhesion. If unsure of cleanliness, always wash surface with an appropriate cleaning solution or solvent (do not use TSP as a cleaner). Remove any peeling and/or unsound coatings. Sand any remaining paint film edges smooth. Allow surface to dry completely before priming. If necessary, spot prime knots and sap streaks with B-I-N® Primer-Sealer before priming with Zinsser Odorless Primer-Sealer Stain Blocker.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN.

PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-Approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

Apply only when air, material, and surface temperatures are between 50-90°F (10-32°C) and relative humidity should not be greater than 85%. Shake can vigorously until the mixing ball begins to rattle. Turn upside down and continue shaking for one minute. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake can occasionally during use. Hold can upright 10-12" from the object and spray in a steady back and forth motion with short 'dusting' strokes, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. To permanently block heavy odors, use Zinsser B-I-N Ultimate Stain Blocker.

Do not use near open flame.

DRY & RECOAT TIMES

Dries to the touch in 30 minutes and can be recoated in 2 hours with latex or oil-based paints. For best results allow the primer to cure overnight when applying solvent-based topcoats.

CLEAN-UP

Wipe off tip before storing. Clean up wet paint with Xylol or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

	TECHNICAL DATA	OLS-02
	ZINSSER® ODORLESS PRIMER-SEALER STAIN BLOCKER	

PHYSICAL PROPERTIES

		ODORLESS PRIMER-SEALER STAIN BLOCKER
Resin Type		Acrylic Copolymer
Pigment Type		Titanium Dioxide
Solvents		Acetone, Isoparaffinic Hydrocarbon
MIR		0.70 Max
Fill Weight		13 ounces
Practical Coverage (assume 15% material loss)		9-12 sq. ft./can (0.84-1.11 m ² /can)
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	30 minutes
	Handle	1 hour
	Recoat	2 hours
	Full Cure	7 days
Flash Point		156°F (-104°C)
Safety		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061

Phone: 877-385-8155
www.rustoleum.com/zinsser

Form: GDH-370
Rev.: 120722