



OUTDOOR  
FILTRATION SYSTEM, PRESSURE

The Outdoor filter is designed for higher ambient temperatures and high-capacity needs, making it ideal for water cooler applications, whether installed in a drinking fountain or in the top of OASIS bottle fillers.

The Outdoor Filter is certified to NSF/ANSI 42 for the reduction of Chlorine, Taste and Odor and Particulate Class I; NSF/ANSI 53 for the reduction of Cyst and Lead and NSF/ANSI 401 for the reduction of Microplastics.

Features:	• Improves the taste and appearance of drinking water
	• Water filtration to reduce turbidity, dirt, rust, sediment, and to inhibit corrosion
	• Automatic shut-off valve inside the head engages as filter is inserted or removed
	• Filter head and cartridge engineered to withstand elevated temperatures for outdoor use*
	• For cold water supply line only
Certified Claims:	• NSF/ANSI 42 for reduction of Chlorine, Taste, Odor and Particulate Class I
	• NSF/ANSI 53 for reduction of Lead and Cyst
	• NSF/ANSI 401 for the reduction of Microplastics
Operating Temperature:	35°F (2°C) to 100°F (38°C)
Ambient Air Temperature:	35°F (2°C) to 122°F (50°C)**
Flow Rate:	1.50 gpm (5.68 Lpm)
Pressure:	20 psi (1.4 bar) to 125 psi (8.6 bar)
Capacity:	4,750 gals (17,980L)
Service Life:	12 months
Sediment:	Down to nominal 0.5 micron
Function:	Mechanical/Chemical Filtration
Installation Location:	For outdoor use

\*When used or stored in non-temperature controlled environments, the unit must be adequately winterized and/or protected from extreme heat to prevent damage.

\*\*A maximum air temperature of 122°F (50°C) has been qualified by the manufacturer.

Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

MODEL: \_\_\_\_\_ QTY: \_\_\_\_\_

PROJECT: \_\_\_\_\_

CONTACT: \_\_\_\_\_

NOTES: \_\_\_\_\_

APPROVAL: \_\_\_\_\_ DATE: \_\_\_\_\_



- Installation**
- Rotate 1/4 turn right or left for installation or removal
  - Universal kit shipped with complete instructions and mounting bracket
- Accessories**
- Replacement Cartridge: # 041667-001
  - Filter Head: # 041666-001
  - Universal Outdoor Filter Kit: # 041253-008
- Certifications/Compliance**
- NSF/ANSI 42, 53, 401 and 372



Specifications subject to change without notice



# OUTDOOR FILTRATION SYSTEM, PRESSURE

## Outdoor Filter Head and Cartridge:

