CHAIN HOIST



Features

- All-steel construction
- Long lasting powder coat finish
- · Minimal load lifting effort
- Weston-Style brake system with twin pawl design Heavy-duty latches
- Zinc plated load chain & hand chain
- Fully-enclosed gearing


- Forged alloy steel hooks
- •Thrust bearing on lower hook
- Individual test certificates & serial numbers

· Load sheave bearings





Standards - CE, ASME B30.16 and AS1418.2



		OZIND025-XXXCH	OZIND005-XXCH	OZIND010-XXCH	OZIND020-XXCH	OZIND030-XXCH	OZIND050-XXCH
	Capacity (tons)	0.25	0.5	1	2	3	5
	Effort to Lift S.W.L (lbs)	55	55	66	88	88	88
	Falls of Chain	1	1	1	1	2	2
	Load Chain Diameter (mm)	4x12	5x15	6x18	8x24	8x24	10x30
		A 10.2	12.8	14.6	17.5	21.7	26.8
		B 4.18	5.35	5.75	7.32	8.2	10.2
	Product Dimensions (in)	C 4.02	5.2	5.98	6.14	6.1	7.4
	Hook-opening, Upper & Lower	D 1.3	1.38	1.73	2	2.28	2.6
	Net Weight (lbs)	4	10	16	19	30	56.2

Standard Lift: 5, 10, 15 and 20 ft.

.25 T Models Standard Lift: 5 and 10 ft. We also do custom rigging

Dimensions and illustrations are for reference only and subject to change without notice. XX in hoist model number indicates length of lift by foot.

















